



Technical datasheet No.: **1157.5**
Product: VALMEX® FR 700 tent
Article No.: 7205 5240

Type of coating and finish		
Type of coating	PVC	
Finish	Acrylic lacquer on both sides, protected against microbial and fungal attack, UV-protected, low-wick	
Flame retardancy	BS 7837, California T 19, CERF Categoria 2, DIN 4102: B1, SIS 650082	
for flame retardancy	always check the validity of fire certificate	
Total weight	700 g/m ²	EN ISO 2286-2
Tensile strength (warp/weft)	3000 / 3000 N/50 mm	DIN 53354, DIN EN ISO 1421/V1
Tear strength (1) (warp/weft)	300 / 300 N	DIN 53363
Adhesion (1)	20 N/cm	LB 3.04-1 (Complan)
Cold resistance	-30 °C	DIN 53361
High Temperature	+70 °C	Directive Complan
Light fastness	>6 Note, Val.	DIN 54004, DIN EN ISO 105 B02
Crack resistance (1)	no cracks	< 100000 x DIN 53359 A
Base fabric		
Material	PES	DIN ISO 2076
Yarn count	1100 dtex	DIN ISO 2060
Weave	L 1/1	

These indicated technical data are based on average results. Due to production procedures slight deviations can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.