

Technical Information

Page 1 of 1

Part No.: 2610.AM160.x (white)

2630.AM160.x (blue)



◆ Untere Gießwiesen 21 ◆ 78247 Hilzingen ◆ Tel.: +49-7731-86880 ◆ Fax: +49-7731-868830

Standard Smock AM-160

Part No.: 2610.AM160.x (white)

2630.AM160.x (blue)

- Static dissipative smock for use in ESD protected areas
- Complies with IEC 61340-5-1
- Breathable
- Tailored in 3/4 design
- Easy snap fastening, hidden snaps
- Conductive yarn woven through the fabric in 4 mm grid.
- UNISEX in S, M, L, XL, XXL and XXXL size



Colour:	white (2610.AM160.x), blue (2630.AM160.x)
Design:	3/4 design, one breast pocket with ESD-logo and two side pockets
Material:	65% polyester, 32% cotton, 3% carbon coated yarn
Weight:	156 g/m ² ± 3%

Durability:

Maintains its electrical properties according to IEC 61340-5-1 after 50 normal washing cycles.

Washing instructions:

- Machine washable, up to 60° C
- Do not bleach
- Medium heat ironing
- Tumble dry, normal, low heat
- Do not allow contact with strong acids or alkali



Product qualification according to IEC 61340-5-1 Ed. 1.0 (2007-08):

	Test method	Limits	Typical values
Point to Point resistance R _{p-p}	IEC 61340-4-9 (2010-01) ANSI/ESD STM 2.1	< 1 x 10 ¹² Ω	10 ⁵ - 10 ⁷ Ω
<i>Environmental conditions: 12 ± 3% RH and 23 ± 2°C (conditioning > 48 hours)</i>			