

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: 1513665 OFFICE DEPOT 400ML HFC AIR DUSTER

Product code: 1513665

Synonyms: OTHER PRODUCT REFERENCES: 417-50-032

Use of substance / preparation: Cleaning Product

Company name: Office Depot International BV
Columbusweg 33
NL - 5928
LA VENLO
The Netherlands
GreenerOffice@officedepot.com
Tel: 0031 77 323 8765
Fax: 0031 77 323 8585
Emergency tel: 0031 77 323 8888 (Mon-Fri 0800-1800)

2. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DIMETHYL ETHER 1-10%
EINECS: 204-065-8 CAS: 115-10-6
[F+] R12

Contains: Tetrafluoroethane Cas Nr 811-97-2 EC: 212-377-0

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact. Frost-bite may occur causing the affected area to become white and numb. Repeated or prolonged skin contact may cause irritation progressing to a burn.

Eye contact: There may be irritation and redness. Direct contact with liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation. Redness. Pain.

Ingestion: There may be irritation of the throat. May cause burns or irritation of the linings of the mouth, throat and gastrointestinal tract.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Overexposure to vapours may result in headache, nausea and drowsiness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

SAFETY DATA SHEET

1513665 OFFICE DEPOT 400ML HFC AIR DUSTER

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Water fog. Do not use heavy water stream.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Remove ignition sources.

7. HANDLING AND STORAGE

Handling requirements: Avoid the formation or spread of dust in the air. Smoking is forbidden. Ensure there is sufficient ventilation of the area. Keep away from food, drink and animal feeding stuffs.

Storage conditions: Store in cool, well ventilated area. The floor of the storage room must be impermeable to prevent the escape of liquids. Keep at temperature not exceeding 50°C. Store above 5°C. Keep away from direct sunlight. Keep away from sources of ignition. Store away from sparks and open flames. Protect from freezing.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: DIMETHYL ETHER
WEL (8 hr TWA): 766 mg/m³ WEL (15 min STEL): 958 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not usually required. Refer to section 15

Hand protection: Only required for prolonged contact Protective gloves.

Eye protection: In case of splashing, ensure source of water is to hand, rinse immediately for 15 minutes holding the eyelids open. Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective gloves for prolonged contact. Avoid skin contact. Contact may cause frostbite.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Colourless

Odour: Ethereal

Solubility in water: Insoluble

Boiling point/range°C: -26

SAFETY DATA SHEET

1513665 OFFICE DEPOT 400ML HFC AIR DUSTER

Melting point/range°C: -100
Autoflammability°C: 300
Vapour pressure: Below 110kPa(1.10bar)
Relative density: >1
pH: Not relevant

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat. Direct sunlight. Hot surfaces. Sources of ignition. Flames. Sparks
Materials to avoid: Strong oxidising agents. Strong acids. Strong bases. Strong oxidizers.
Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Chronic toxicity: Danger of cumulative effects through inhalation. Danger of cumulative effects in contact with the skin.
Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water.
Persistence and degradability: No data available.
Bioaccumulative potential: No data available.
Other adverse effects: No data available. Germany: WGK 1 (VwVwS vom 17/05/99, KBws) Tetrafluorethane dpo
Ozone Destruction Potential = 0

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1950 **ADR Class:** 2
Classification code: 5A
Shipping name: AEROSOLS
Labelling: 2.2



SAFETY DATA SHEET

1513665 OFFICE DEPOT 400ML HFC AIR DUSTER

IMDG / IMO

UN no: 1950	Class: 2
EmS: 2-13	Marine pollutant: .
Labelling: 2.2	

IATA / ICAO

UN no: 1950	Class: 2
Labelling: 2.2	

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S3/9: Keep in a cool, well ventilated place.

S23: Do not breathe vapour.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S33: Take precautionary measures against static discharges.

Can cause frostbite.

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Spray in short bursts

Do not use for any purpose other than for the one that it is intended

10 % by mass of the contents are flammable.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.