



## Declaration of compliance

Item number: 70375  
Item name: Stiff Tank Brush, White

Producer: **Vikan A/S**  
Rævevej 1  
7800 Skive  
Denmark  
Tel.: +45 96 14 26 00

Materials: **Polypropylene 97 %, white masterbatch 2 % and defoaming agent 1 % in the brush block**

### **Polypropylene:**

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs.

This polypropylene grade contains the following "dual use" additives: Glycerol monostearat, calcium stearat and talc.

No monomers and additives with specific migration limit (SML) are used.

### **White masterbatch:**

Monomers and additives used to manufacture this grade are listed in Directive 2002/72/EC with current amendments, relating to plastic materials and articles intended to come into contact with foodstuffs.

White masterbatch contains the following "dual use" additive: TiO<sub>2</sub>.

No monomers and additives with specific migration limit (SML) are used.

### **Defoaming agent:**

Monomers and additives used to manufacture this grade are listed in Directive 2002/72/EC with current amendments, relating to plastic materials and articles intended to come into contact with foodstuffs.

### **Filaments made from polybutyleneterephthalate (PBT)**

The raw materials (polymer, master batches and additives) used to manufacture these filaments are declared by supplier to be strictly in conformity with the Directive 2002/72/EC relating to materials to be used in contact with foodstuffs.

### **Stainless steel thread**

No restrictions or specific migration levels.

FDA: All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) CFR 21.

General: In accordance with EU Commission Regulation no. 1935/2004 of October 2004 the product is intended for food contact. The handle can be marked with the "glass & fork" symbol on the packaging or by labeling.

The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).

Overall migration tests are made on similar products. The products meet the requirements regarding overall migration to 50 % ethanol, 3 % acetic acid and tenax (for non liquid foodstuff) and isooctane (substitute to olive oil).

Food contact: No limitation

Usage temperature: Min. temp.: -20 °C  
Max. temp.: 80 °C

Vikan equipment is not supplied to any microbial specification.

It is recommended that equipment is cleaned, disinfected and sterilised, as appropriate to its intended use, before use.

It is also important to clean, disinfect and sterilise equipment after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.

Appropriate equipment decontamination will minimise risk of microbial growth and cross contamination and maximise the efficiency and durability of the equipment.

Max. Wash temp.: 121 °C

Date: 6th October 2011

Made by: Inger Arensbach  
Quality- and environmental manager