SAFETY DATA SHEET

Husholdningssprit

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Husholdningssprit

Product no.

724

Unique formula identifier (UFI)

No data available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Professionel uses.

Use descriptors (REACH)

Sector of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product categories	Description
PC35	Washing and Cleaning Products (including solvent based products)
Process Categories	Description
PROC 28	Manual maintenance (cleaning and repair) of machinery
Environmental release categories	Description
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8b	Wide dispersive indoor use of reactive substances in open systems
ERC8d	Wide dispersive outdoor use of processing aids in open systems

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Jysk Kemi Service A/S

Gl. Struervej 50

7500 Holstebro

Denmark

+45 9740 3133

+45 9740 4846

www.jyskkemi.dk

Contact person

Husholdningssprit Page 1 of 12

Rikke Hunskjær

E-mail

rikke@jyskkemi.dk

SDS date

2021-05-12

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour.

Safety statement(s)

General

P102, Keep out of reach of children.

Prevention

P210, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233, Keep container tightly closed.

Posponso

P370+P378, In case of fire: Use water mist / carbon dioxide / alcohol-resistant foam to extinguish.

Storage

P403+P235, Store in a well-ventilated place. Keep cool.

Disposal

P501, Dispose of contents/container to an approved waste disposal plant.

Hazardous substances

No special

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/substance Identifiers % w/w Classification Note	
---	--

Husholdningssprit Page 2 of 12



ethanol CAS No.: 64-17-5 95-100% Flam. Liq. 2, H225

EC No.: 200-578-6

REACH: 01-2119457610-43-

XXXX

Index No.: 603-002-00-5

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. Other information

[1] European occupational exposure limit

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Husholdningssprit Page 3 of 12

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical / lighting / ventilating]equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

> 0°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

Husholdningssprit Page 4 of 12

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol

Long term exposure limit (8 hours) (ppm): 1000 Long term exposure limit (8 hours) (mg/m³): 1920

__

butanone

Long term exposure limit (8 hours) (ppm): 200 Long term exposure limit (8 hours) (mg/m³): 600 Short term exposure limit (15 minutes) (ppm): 300

Short term exposure limit (15 minutes) (mg/m³): 899

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020)

DNEL

No data available

PNFC

No data available

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

Work situation	Recommended	Type/Category	Standards
	No special when used as intended	-	-

Hand protection

Husholdningssprit Page 5 of 12

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
	Butyl	0.7	> 480	EN374-2, EN374-3, EN388, EN421	
e protection					
Work situation	Туре		Standards		

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Colourless

Odour / Odour threshold

Characteristic

рН

Testing not relevant or not possible due to nature of the product.

Density (g/cm³)

0.79

Kinematic viscosity

Testing not relevant or not possible due to nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

78.00 °C

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Relative vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

13.00 °C

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Product/substance butanone

Test method

Species Rat
Route of exposure Oral
Test LD50

Result > 2193 mg/kgbw

Other information

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product/substance butanone

Test method

Species Mouse

Conclusion No adverse effect observed

Other information

Husholdningssprit Page 7 of 12



Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Long term effects

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

No special

Other information

ethanol has been classified by IARC as a group 1 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance butanone

Test method

Species Fish

Compartment

Duration 96 hours
Test LC50
Result 2993 mg/L

Other information

Product/substance butanone

Test method

Species Daphnia

Compartment

Duration 48 hours
Test EC50
Result 308 mg/L

Other information

Product/substance butanone

Test method

Species Algae

Compartment

Duration 72 hours
Test EC50
Result 1972 mg/L

Husholdningssprit Page 8 of 12



Other information

12.2. Persistence and degradability

Product/substance butanone Biodegradable Yes

Test method OECD 301 D
Result 98%

12.3. Bioaccumulative potential

Product/substance butanone

Test method

Potential No

bioaccumulation

LogPow 0,3

BCF No data available

Other information

12.4. Mobility in soil

butanone

LogKoc = 0.31597, High mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

Avoid discharge to lakes, streams, sewers, etc.

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

20 01 13* Solvents

Waste Group C

Waste Group C

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

This product is within scope of the regulations of transport of dangerous goods.

Tunnel restriction

code

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

ADR/F	RID				
	UN- or ID	UN proper shipping name	Labels	PG	

1170 ETHANOL SOLUTION (ETHYL ALCOHOL 3 II 2 (D/E)

SOLUTION)

IMDG

UN- or ID UN proper shipping name Labels PG **EmS** number 1170 ETHANOL SOLUTION (ETHYL ALCOHOL II F-E, S-D

SOLUTION)

MARINE POLLUTANT

number

No

IATA

UN- or ID number	UN proper shipping name	Labels	PG
1170	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	3	II

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes Additional information

Tactile warning.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

Husholdningssprit Page 10 of 12

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H336, May cause drowsiness or dizziness.

H319, Causes serious eye irritation.

EUH066, Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC 28 = Manual maintenance (cleaning and repair) of machinery

PC35 = Washing and Cleaning Products (including solvent based products)

ERC8a = Wide dispersive indoor use of processing aids in open systems

ERC8b = Wide dispersive indoor use of reactive substances in open systems

ERC8d = Wide dispersive outdoor use of processing aids in open systems

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol

of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit.

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

Husholdningssprit Page 11 of 12

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of physical hazards has been based on experimental data. The safety data sheet is validated by

RH

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en

Husholdningssprit Page 12 of 12