



CE

Koalescensudskiller

CE overensstemmelseserklæring

Det erklæres hermed, at Scan-Plast koalescensudskillere, type 3, 6, 8, 10, 12, 15, 20, 24, 30, 35, 48, 62, 79 og 100 l/sek. klasse 1 og 2 er i overensstemmelse med kravene af Byggevaredirektivet 89/106/EEC og ændringsdirektivet 93/68/EEC.

Harmoniseret standard

EN 858-1.

Udskillere til letflydende væsker (f.eks. olie og benzin)
– Del 1: Designprincipper, ydeevne og prøvning, mærkning og kvalitetskontrol.

Rapport

SPDTI rapport nr. 2009.09.11.0062.0010.

Materiale/kvalitet

Glasfiberarmeret polyester (GAP).
Overensstemmelse mellem produktdirektiver og internt kvalitetssystem er verificeret.

Brandforhold

Koalescensudskilleren er beregnet for nedgravning med deraf følgende minimale brandrisici.

Coalescence separator

CE Declaration of Conformity

Hereby it is declared, that Scan-Plast coalescence separators, type 3, 6, 8, 10, 12, 15, 20, 24, 30, 35, 48, 62, 79 and 100 l/sec. class 1 and 2 are in conformity with the requirements of the Construction Products Directive 89/106/EEC and the Council Directive 93/68/EEC.

Harmonized standard

EN 858-1.

Separators for light liquids (e.g. oil and gasoline)
– Part 1: Principles for design, performance and testing, marking and quality control.

Report

SPDTI report no. 2009.09.11.0062.0010.

Material/quality

Fiberglass reinforced polyester (FRP).
Conformity between product directives and internal quality system is verified.

Fire conditions

The coalescence separator is for underground installation with a following minimum of fire risk.

Holstebro, d. 14.09.2009

Frank Svalgaard
Udviklingschef