

## TDS og instruction

### Væg 5

#### Wall paint for interior use

Item no. 181-XXXX04 PR no. 2360967

UFI: RRHA-7V3F-020P-8VDA



#### Product description

Vægmalning 5 is a flat wall paint, that provides a nice, smooth and easy-to-use finish.

#### Areas of application

Painting of interior walls and ceilings in dry rooms, where no special requirements on wear resistance and washability, needs to be met.

#### Substrate

Substrate must be clean, dry, firm and free from staining, as well as suitable for painting.

Porous, untreated substrate such as plaster, concrete etc. must be primed with micro-dispersion primer before paint.

Staining substrates must be thoroughly cleaned and washed with basic cleaner, and then primed with a suitable stain stopper.

#### Treatment

Stir well before and during use.

Apply with paintbrush, paint roller or sprayer.

Drying time between coats must be min. 4-6 hours.

Expect application of min. 2 coats of paint.

#### Consumption

Consumption depends on absorption of present substrate.

Painting on new plaster, approx. 4 m<sup>2</sup>/l/layer.

When repainting previously painted surfaces, where there is no change in colour, the consumption is approx. 8 m<sup>2</sup>/l.

When changing colour, the consumption is approx. 4-5 m<sup>2</sup>/l depending on colour.

Untreated wall covering can be primed with a high build primer for full and uniform finish.

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

**Type:** Wall paint

#### Areas of application:

Interior walls and ceilings in dry rooms

**Binder:** Styren acrylic

**Density:** Approx. 1.3 kg/l ISO 2811

**Viscosity (at 20°C):** cP 3000

**Gloss (v. 60° angle):** Approx. 5, flat

**Consumption:** 4-8 m<sup>2</sup>/l

#### Drying time (20°C - 85% RH):

4-12 hours, depending on layer thickness, absorbency of the substrate, temperature, humidity and ventilation

#### Next coat (at 20°C - 85% RH):

When dry, but min. 4 hours

#### Curing time (at 20°C - 85% RH):

Fully cured after 7 days

#### Application temperature:

Developed for use at 10°C-25°C  
Min. +10°C - Max. 30°C  
(substrate and surroundings)

#### Humidity:

Best at 60%-65% RH  
Min. 40% max. 80% RH

#### Cleaning tools:

Water and soap

#### Storage:

Store at +5°C-+25°C, not in direct sunlight and inaccessible to children

#### Shelf life:

Min. 24 months from production date when stored correctly (Batch no. yymmdd)

**Packaging:** 10 litre bucket

**Quantity per colli:** 1 - 11 - 44 pcs

**Colours:** White, light off-white, off white, black and base C for tinting

**VOC value:** <30 g/l

**EU VOC limit value (2010):**

Cat A/i: 30 g/l

**CLP symbols:** None

**CLP signal word:** None

**MAL code:** 00-1

**Washable:** Class 2 EN13300

**Permeability:** Class 1 EN 7783-2

**Adhesion:** GT≤1 jf. EN 2409

**Document date:** 30-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro  
+45 9610 5080 • info@promal.dk • www.promal.dk