

## TDS og instruction

### Køkken & bad 25

Paint for interior & exterior use

Item no. 186-XXXXXX PR no 2360959

UFI: JNHA-QVE1-Q206-KHT8



Køkken & bad 25 is a semi-matt paint for walls and facades. The paint provides a nice, smooth and very durable finish.

#### Areas of application

For painting interior walls and ceilings in bathrooms, kitchens, hall rooms, laundry and other rooms, where washable or weather resistant paint is required.

#### Substrate

Substrate must be clean, dry, firm, free from staining and suitable for painting.

Porous, untreated substrate such as plaster, concrete etc. must be primed with micro-dispersion primer.

Staining substrate must be thoroughly cleaned, and primed with suitable primer.

#### Treatment

Stir well before and during use.

Apply with paintbrush, paint roller or paint sprayer.

Drying periods between the layers must be min. 4-6 hours

Expect application of minimum 2 coats of paint.

#### Consumption

Consumption depends on absorption and structure of substrate.

New paint on primed, smooth-plastered wall approx. 4 m<sup>2</sup>/l.

Repainting of previously painted surfaces, without colour change, is approx. 8 m<sup>2</sup>/l.

When changing colour, approx. 4-5 m<sup>2</sup>/l.

Wall covering that has not previously been painted can advantageously be primed with a rich primer.

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

**Type:** Wall paint

#### Areas of application:

Interior walls and ceilings and exterior walls

**Binder:** Acrylic

**Density:** Approx. 1.2 kg/l ISO 2811

**Viscosity (at 20°C):** approx. cP 3000

#### Gloss (v. 60° angle):

Approx. 25, semi matt

#### Consumption:

3-6 m<sup>2</sup>/l - new paint

4-10 m<sup>2</sup>/l - repaint

#### Drying time (20°C - 85% RH):

4-12 hours, depending on layer thickness, absorbency of the substrate, ambient temperature, humidity and ventilation

#### Next coat (at 20°C - 85% RH):

When dry, but min. 12 hours

#### Curing time (at 20°C - 85% RH):

Fully cured after 7 days

#### Application temperature:

Developed for use at 10°C-25°C

Min. +5°C - Max. 30°C

(substrate and surroundings)

#### Humidity:

Best at 60%-65% RH

Min. 40% max. 80% RH

#### Cleaning tools:

Water and soap

#### Storage:

Store at +5°C-+25°C, not in direct sunlight and inaccessible to children

#### Shelf life:

Min. 24 months from production date when stored correctly

(Batch no. yymmdd)

**Packaging:** 3 and 10 litre bucket

**Colours:** White, light off-white, off-white and base C for tinting

**VOC value:** <30 g/l

**EU VOC limit value (2010):**

Kat A/a: 30 g/l

**CLP symbols:** None

**CLP signal word:** None

**MAL code:** 00-1

**Washable:** Class 1 EN13300

**Permeability:** Class 1 EN 7783-2

**Adhesion:** GT≤1 jf. EN 2409

**Document date:** 20-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro  
+45 9610 5080 • info@promal.dk • www.promal.dk