

TDS og instruction

Universalrens koncentrat 50

Concentrated cleaning agent

Item no. 846-00050 PR no. 2361206

UFI: RNMA-EVJX-E20H-RG6H



Universalrens koncentrat is an effective professional cleaning agent for exterior areas.

Areas of application

For maintenance cleaning and for cleaning before painting. Use for cleaning roof, patio, deck, facade, plinth, tile, gable, eave, fence, terrace, wood etc.

Effectively loosens/dissolves dirt and remains of plant material.

Substrate

For optimal effect, sweep away any loose material prior to the application.

Treatment

Mix with water in a ratio of 1:50.

In case of heavy soiling, the product can be used in a more concentrated form. Dilute product accordingly at least 1:10.

Apply cleaner with brush, non-atomizing sprayer or foam nozzle.

The surface can advantageously be processed mechanically.

When used in concentrations above 1:10, rinse with water after allowing to sit appropriately.

When used 1:50 the cleaner doesn't have to be rinsed away but it is an advantage to do so, to remove dissolved dirt.

Restrictions

The product's effectiveness is significantly reduced at temperatures below 10°C.

Warning and transport

Protect animals and plant growth against splash/spray, as plant cell walls and chloroplasts can suffer irreparable damage and therefore wither and die.

The product corrodes to glass and metals!

Avoid leading waste water into the aquatic environment.

UN 1760

CORROSIVE LIQUID, N.O.S.

(Benzyl-C12-14-alkyldimethylammonium chlorides)

Transport hazard class 8 packaging group II

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

Type: Cleaning agent

Areas of application:

Exterior cleaning

Binder:

Quaternary ammonium compounds/
benzalkonium chloride
cationic surfactants: >30%

Thinner: 1:50

Density: Approx. 0.99 kg/l ISO 2811

Concentration: Approx. 50%

Consumption:

Ready mix approx. 10-15 m²/litr.

Impact time at 23°C/50% RH:

Depending on dilution

1:50 – 1 week

1:20 – 2-5 days

1:10 – 4 hours -1 day

Temperature: Use at 10°C-25°C
(substrate and surroundings)

Higher temperatures = quick impact

Lower temperatures = slow impact

Cleaning tools:

Water

Storage:

Store at +5°C-+25°C, not in
direct sunlight and inaccessible to
children

Shelf life:

Min. 24 months from production
date when stored correctly
(Batch no. yymmdd)

Packaging: 20 and 1,000 litres

Colour: Clear/yellowish

CLP signals:



CLP signal word Danger

MAL code: 00-4

Protective gear:



In case of insufficient ventilation, use
filter mask A2

Document date: 20-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro
+45 9610 5080 • info@promal.dk • www.promal.dk