Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or | trade mark: mylight.me |
|---------------------|---|
| Supplier's address: | Compliance Department, Moegelgaardsvej 19, 8520 Lystrup, DK |

| Model identifier: 0 | 144030102 |
|---------------------|-----------|

| Tyne | of light sou | ırca. |
|------|--------------|-------|
| IVDE | OI HEHL SOL | JILE. |

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|--------------|---------------------------------|----------------------------|
| Light source cap-type | DC Connector | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with specific dimmers |

Product parameters

| | | Fioduct parai | | | |
|--|--|-------------------------|--|--------------|--|
| Parameter | | Value | Parameter | Value | |
| | General product parameters: | | | | |
| | mption in on- 100 h), rounded st integer | 4 | Energy efficiency class | G | |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 351 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 777 | |
| On-mode pressed in W | oower (P _{on}), | 3,8 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 85 | |
| Outer | Height | 2 | Spectral power | See image | |
| dimensions | Width | 8 | distribution in the | in last page | |
| | | | _ | Page 1 / 3 | |

| without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | Depth | 1 500 | range 250 nm to 800 nm, at full-load | |
|--|--------------------------|-------|---|-------|
| Claim of equival | ent power ^(a) | - | If yes, equivalent power (W) | - |
| | | | Chromaticity | 0,440 |
| | | | coordinates (x and y) | 0,408 |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rende | ring index value | 21 | Survival factor | 0,50 |
| the lumen main | tenance factor | 0,70 | | |

(a)'-': not applicable;

(b)'-': not applicable;

