

TDS og instruction

Græsstribemaling Klar-til-brug

Paint for lines on grass and gravel courts – ready for use

Item number 133-003340 PR number 4088151

UFI: 8MNA-0V59-S20Y-17M7



Græsstribemaling Klar-til-brug is a marking paint with special binders and pigments:

- Gentle on grass and plants
- Ultimate result
- Easy to use

Fantastic whiteness is achieved, with just one application. The paint is quick-drying and gives a particularly durable line.

Areas of application

The paint is ready for use in all high-pressure machines. Specially developed for areas where a very white and clear line is desired, using a very small amount of paint. Consumption is just 1½-2 litre per football field.

Substrate

Grass and gravel lanes, such as football fields, tennis courts and pitches for e.g. frisbee golf, crolf, soccer golf, petanque, grass- or gravel playgrounds, etc.

Treatment

Shake/stir carefully before use.
Do not dilute, ready to use.
Apply with a high-pressure machine.
Clean the machine immediately after use.

Note

Must be stored and transported frost-free.
Replace the lid immediately after use.
In case of splashes in the eyes, rinse immediately with clean water.

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

Type: Grass stripe paint

Areas of application:

Lines on grass and gravel and markings

Binder: Styrene acrylic

Density: approx. 1.25 kg/l ISO 2811

Viscosity (at 20°C): DIN4 14-20

Gloss (v. 60° angle): Approx. 3, matt

Consumption:

1.5-2 ltr/lane depending on the nature of the substrate, the nozzle used and application rate

Drying time (at 20°C/RH 80%):

Approx. 30 minutes
Rainproof when dry
Depending on current conditions

Application temperature:

Developed for use at 10°C-25°C
Min. +5°C - Max. 30°C
(substrate and surroundings)

Humidity:

Best at 60%-65% RH
Mine. 40% max. 80% RH

Cleaning tools:

Water and soap

Storage:

Store at +5°C-+25°C, not in direct sunlight and inaccessible to children

Shelf life: Min. 24 months from production date (Batch no. yymmdd) when stored correctly

Packaging: 10 litres

Quantity per colli: 1 - 10 - 60 pcs

Colours: White

VOC value: <30 g/l

EU VOC limit value (2010):

Cat A/i: 140 g/l

CLP symbols: None

CLP signal word: None

MAL code: 00-1

Document date: 20-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro
+45 9610 5080 • info@promal.dk • www.promal.dk