

# Strukturmalning

Structuring paint.

Item no. 151-001104 PR no. 2361142

## Product description

Strukturmalning is a special paint containing quartz sand. The paint is designed to render the treated surface a structured and durable finish.

## Application areas

Exterior & interior walls, facades & ceilings, where ever a slightly coarse and cement-plastered look is desired. Strukturmalning is suitable for hiding substrate unevenness.

## Substrate

Substrate must be clean, dry, firm and free from staining. Porous, untreated substrate such as plaster, concrete etc. must be primed with micro dispersion primer. Staining substrates must be thoroughly cleaned, and primed with suitable primer.

## Use

Stir extremely well before and during use. Use a mixer for electric drill. The paint has thixotropic properties; it becomes less viscous when stirred and more viscous when left at rest.

Apply ample amounts of paint, using trowel, paintbrush or sturdy roller. Do not apply more than 4-5 mm/application

If product is applied with trowel, patterns can be made with paint roller or paintbrush, in applied material.

## Top coat

Strukturmalning must be painted with ordinary wall or facade paint, depending on easy-clean requirements.

The aforementioned information is based on laboratory tests & practical testing. A general responsibility for paintjobs can not be given, due to the different situations that can be expected, depending on application, surface, method etc. the user should, at any time, require new and revised datasheets. We reserve the right to make changes and we make reservations against misprint. *When consumption of a paint exceeds one or more batches, these should be intermixed, to avoid gloss and/or colour difference.*

**Type:** Structuring paint.

**Application areas:** Exterior & interior walls and facades.

**Binder:** Styren acrylate mix.

**Density:** Approx. 1.6 kg/ltr.

**Solids:** Approx. 65 %

**Viscosity:** cP 3000-4000. The product is thixotropic and becomes more fluid during processing.

**Consumption:** 2-5m<sup>2</sup>/ltr depending on layer thickness.

**Dry:** 4-12 hours, depending on layer thickness.

**Next coat after:** min. 24 hours.

**Can be sanded after:** min. 24 hours.

**Fully durable:** 7 days.

**Temperature:** Use between 10°C-25°C

**Air humidity:** optimal at 60%-65% RH  
Min. 40% max. 80% RH

**Cleaning of tools:** Water and detergent.

**Storage:** Store at +5°C-+25°C. Not in direct sunlight, and out of reach of children.

**Shelf life:** 9 months from production date when stored correctly (Batch no yymmdd)

**Packaging:** 10 litre bucket.

**Colour:** white

**Product VOC:** <30 g/l

**EU VOC limit (2010):**

Kat A/a: 30 g/l

**CLP symbol:** none

**CLP signal word:** none

**Safety (MAL-code):** 00-1

**Document date:** 070217

**Revised:** 011118