

## TDS og instruction

### Væg & facade 5

Pure acrylic paint for interior & exterior use on walls & facades

Item no 172-001104 PR no 2360967



Væg & facade 5 is an extremely durable and flat wall paint. It provides a nice, clean and easy-to-clean surface that is both dirt repellent and durable. Wall & Facade 5 can withstand scrubbing.

#### Areas of application

Exterior & interior walls, facades & ceilings. Wall & façade 5 is suitable for high load areas, such as laundry rooms, changing rooms, hallways etc.

#### Substrate

Substrate must be clean, dry firm, free from staining and suitable for painting. Porous, untreated substrate such as plaster, concrete etc. must be primed with micro dispersion primer. Staining substrates must be thoroughly cleaned, and primed with suitable primer.

#### Treatment

Stir extremely well before and during use. Apply with paintbrush, paint roll or sprayer. Drying time between the coats must be min. 4-6 hours, depending on ambient environment. Expect application of minimum 2 coats of paint.

#### Consumption

Consumption depends on condition and absorption of present substrate and colour.

- New paint on plaster, approx. 4 m<sup>2</sup>/l.
- Repaint/ refreshing of previously painted surface approx. 6-8 m<sup>2</sup>/l.
- Change of colour, approx. 4 m<sup>2</sup>/l.

When changing color from colored to white, it is advantageous to prime with a light gray before painting with white. When painting over decoration or repairs, paint those first and then the whole surface.

It is an advantage to prime untreated wall-cover with a high build primer-paint, prior to painting.

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

**Type:** Wall & facade painting

**Areas of application:** Exterior & interior walls and facades

**Binder:** Acrylic

**Density:** Approx. 1,25 kg/l ISO 2811

**Viscosity (at 20°C):** cP 2800-3000

**Gloss (v. 60° angle):** Approx. 5, matt

**Consumption:** 5-8m<sup>2</sup>/l

**Drying time:** 4-12 hours, depending on layer thickness, absorbency of the substrate, temperature, humidity and ventilation

**Next coat (at 20°C - 85% RH):** When dry, but min. 4 hours

**Curing time (at 20°C - 85% RH):** Fully cured after 7 days

**Application temperature:** Developed for use at 10°C-25°C  
Min. +10°C - Max. 30°C  
(substrate and surroundings)

**Humidity:** Best at 60%-65% RH  
Min. 40% max. 80% RH

**Cleaning tools:** Water and soap

**Storage:** Store at +5°C-+25°C, not in direct sunlight and inaccessible to children

**Shelf life:** Min. 24 months from production date (Batch no. yymmdd) when stored correctly

**Packaging:** 10 litre bucket

**Colours:** White

**VOC value:** <30 g/l  
**EU VOC limit value (2010):** Cat A/i: 30 g/l

**CLP symbols:** None  
**CLP signal word:** None

**MAL code:** 00-1

**Washable:** class 2 EN13300  
**Permeability:** class 1 EN 7783-2  
**Adhesion:** GT≤1 jf. EN 2409

**Document date:** 20-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro  
+45 9610 5080 • info@promal.dk • www.promal.dk