

TDS og instruction

Væg & façade 10

Pure acrylic paint for interior & exterior use.

Item no 174-001104 PR no 4089314

UFI:



Væg & facade 10 is an extremely durable and matt wall paint. It provides a nice, clean and easy-to-clean surface that is both dirt repellent and durable. Wall & Facade 10 can withstand scrubbing.

Areas of application

Exterior & interior walls, facades & ceilings. Wall & façade 10 is especially suitable for high load areas, such as laundry rooms, changing rooms, hallways etc.

Substrate

Substrate must be clean, dry firm, free from staining and suitable for painting.

Porous, untreated substrate such as plaster, concrete etc. must be primed with micro dispersion primer.

Staining substrates must be thoroughly cleaned, and primed with suitable primer.

Treatment

Stir extremely well before and during use.

Apply with paintbrush, paint roll or sprayer.

Drying periods between the layers must be min. 4-6 hours

Expect application of minimum 2 coats.

Consumption

Consumption depends on condition, colour and absorption of present substrate.

- New paint on plaster, approx. 4 m²/l.
- Repaint/ refreshing of previously painted surface approx. 6-8 m²/l.
- Change of colour, approx. 4 m²/l.

When changing color from coloured to white, it is advantageous to prime with a light gray before painting with white. When painting over decorations or repairs, paint these before painting the whole surface.

It is an advantage to prime untreated wall-cover with a high build primer-paint, prior to painting.

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

Type: Wall & facade painting

Areas of application:

Exterior & interior walls and ceilings

Binder: Acrylic

Density: Approx. 1.28 kg/l ISO 2811

Viscosity (at 20°C): cP 2,800-3,000

Gloss (v. 60° angle): Approx. 10, matt

Consumption: 5-8 m²/l

Drying time: 4-12 hours, depending on layer thickness, absorbency of the substrate, temperature, humidity and ventilation

Next coat (at 20°C - 85% RH):

When dry, but min. 4 hours

Curing time (at 20°C - 85% RH):

Fully cured after 7 days

Application temperature:

Developed for use at 10°C-25°C

Min. +5°C - Max. 30°C

(substrate and surroundings)

Humidity:

Best at 60%-65% RH

Min. 40% max. 80% RH

Cleaning tools:

Water and soap

Storage:

Store at +5°C-+25°C, not in direct sunlight and inaccessible to children.

Shelf life:

Min. 24 months from production date (Batch no. yymmdd) when stored correctly

Packaging: 10 litre bucket

Quantity per colli: 1 - 11 - 44 pcs

Colours: White

VOC value: <30 g/l

EU VOC limit value (2010):

Cat A/a: 30 g/l

CLP symbols: None

CLP signal word: None

MAL code: 00-1

Washable: Class 2 EN13300

Permeability: Class 1 EN 7783-2

Adhesion: GT≤1 jf. EN 2409

Document date: 24-08-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro
+45 9610 5080 • info@promal.dk • www.promal.dk