

TDS og instruction

Væg 10

Wall paint for interior use

Item no. 183-00XXXX PR no 2360967

UFI: RRHA-7V3F-020P-8VDA



Product description

Vægmaling 10 is a matt wall paint that provides a nice, smooth and easy-to-clean finish.

Areas of application

Painting of interior walls and ceilings in dry rooms, where requirements on very high wear resistance and washability, are not essential.

Substrate

Substrate must be clean, dry, firm, free from staining and suitable for painting.

Porous, untreated substrate, such as plaster, concrete etc., must be primed with micro dispersion primer before paint.

Staining substrates must be thoroughly cleaned and washed with soapy water prior to being primed with a stain stopper.

Treatment

Stir well before and during use.

Apply with paintbrush, paint roller or sprayer.

Drying time between coats must be min. 4-6 hours.

Expect application of min. 2 coats.

Consumption

Consumption depends on absorption of present substrate.

Painting on new plaster, approx. 4 m²/l/layer.

When repainting previously painted surfaces, where there is no change in colour, the consumption is approx. 8 m²/l.

When changing colour, the consumption is approx. 4-5 m²/l depending on colour.

New wall coverings can be primed with a high build primer for full and uniform finish.

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

Type: Wall paint

Areas of application:

Interior walls and ceilings in dry rooms

Binder: Styren acrylic

Density: Approx. 1,2 kg/l ISO 2811

Viscosity (at 20°C): cP 3000

Gloss (at 60° angle): approx. 10, matt

Consumption: 4-8 m²/l

Drying time (20°C - 85% RH):

4-12 hours, depending on layer thickness, absorbency of the substrate, temperature, humidity and ventilation

Next coat (at 20°C - 85% RH):

When dry, but min. 4 hours

Curing time (at 20°C - 85% RH):

Fully cured after 7 days

Application temperature:

Developed for use at 10°C-25°C
Min. +10°C - Max. 30°C
(substrate and surroundings)

Humidity:

Best at 60%-65% RH
Min. 40% max. 80% RH

Cleaning tools:

Water and soap

Storage:

Store at +5°C-+25°C, not in direct sunlight and inaccessible to children

Shelf life:

Min. 24 months from production date when stored correctly
(Batch no. yymmdd)

Packaging: 3 litre and 10 litre bucket

Colours: White, light off-white, off white and base C for tinting

VOC value: <30 g/l

EU VOC limit value (2010):

Cat A/a: 30 g/l

CLP symbols: None

CLP signal word: None

MAL code: 00-1

Washable: Class 2 EN13300

Permeability: Class 1 EN 7783-2

Adhesion: GT≤1 jf. EN 2409

Document date: 8-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro
+45 9610 5080 • info@promal.dk • www.promal.dk