

TDS og instruction

Microdispers Unigrunder

Micro dispersion primer

Item no. 442-0011xx PR no. 2361134

UFI: 5JKA-UVKS-F203-41MP



White pigmented micro dispersion primer for priming of absorbent substrates before painting and wallpapering. Initial white colour and fastening primer in one go.

Areas of application

Priming of plaster, plasterboard, concrete, mud, putty and lime. When using white pigmented primer, base colour and fastening primer is applied in one and same workflow. Only for interior use.

Substrate

Substrate must be clean, dry, firm, free from staining and suitable for painting.

Clean and rinse whitewashed surfaces until rinsing water is clear and free from lime.

Staining substrates such as nicotine, stains, soot etc. must be cleaned, primed with micro dispersion primer, thereafter; an appropriate stain stopper.

Treatment

Stir well before and during use. Apply with paintbrush or paint roller.

Prime one time only, substrate must absorb the micro dispersion primer. Do not use the primer as finishing paint.

Note:

If primed substrate appears glossy when dry, sand before painting. Excessive priming causes bad adhesion.

Apply appropriate paint within two weeks after priming with micro dispersion primer.

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

Type: Micro dispersion primer

Areas of application:

Absorbent mineral substrates. Interior use only

Binder: Acrylic micro dispersion

Thinning: Dilute with water

Density: Approx. 1,2 kg/l ISO 2811

Viscosity (20°C): cP 1300

Consumption: 60-70 ml/m², depending on application method and substrate

Application:

Paintbrush, paint roll or sprayer

Drying time at 20°C/60% RH: 4 hours

Application temperature:

Developed for use at 10°C-25°C
Min. +5°C - Max. 30°C
(substrate and surroundings)

Humidity:

Best at 60%-65% RH
Min. 40% max. 80% RH

Cleaning tools:

Water and soap

Storage:

Store at +5°C-+25°C, not in direct sunlight and inaccessible to children

Shelf life:

Min. 24 months from production date when stored correctly
(Batch no. yymmdd)

Packaging: 10 litre bucket

Colours: White/whiteish

VOC value: <30 g/l

EU VOC limit value (2010):
Kat A/a: 30 g/l

CLP symbols: None

CLP signal word: None

MAL code: 00-1

Permeability: Class 1 EN 7783-2

Document date: 20-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro
+45 9610 5080 • info@promal.dk • www.promal.dk