

TDS og instruction

Specialfortynder 520 (xylene)

Cleaner and thinner

Item number 900-0000xx PR number 1427912

UFI:



Xylene is a solvent that is mainly used for degreasing.

Areas of application

For cleaning and degreasing before painting or coating as well as for diluting certain types of paint materials.

Treatment

Concentrated or water-diluted xylene is applied with a brush or cloth. Avoid application methods that create spray mist. The treated surface can advantageously be processed mechanically.

Limitations

Do not work with thinner on hot surfaces as harmful vapours will form. Avoid sparks and open flame. Highly flammable liquid and vapour.

Warning/Safety

Use gloves.
Avoid contact with skin, hair and eyes.
Use eye protection and respiratory protection with filter A - class 1/brown
Keep out of reach of children.

Transport

UN 1307 - XYLENES, N.O.S. (Xylen).
Transport hazard class 3 packaging group III

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

Type: Thinner

Areas of application:
Cleaning and dilution

Active substances:
Xylene >= 75%
Ethylbenzene <= 25%
Toluene <= 0,1%

Density: Approx. 0.87 kg/l ISO 2811

Concentration: 99%

Boiling point: 136-145°C

Flash point: 24°C

Self-ignition temperature: 460°C

Odours: Aromatic

Warning:
Avoid contact with strong acids and strong oxidizing agents.
Avoid heating and contact with ignition sources

Application temperature:
Developed for use at 0°C-25°C
(substrate and surroundings)

Humidity:
Best at 60%-65% RH
Min. 40% max. 80% RH

Cleaning tools:
Water

Storage:
Store at +0°C-+25°C, not in direct sunlight and inaccessible to children

Shelf life:
Min. 24 months from production date when stored correctly
(Batch no. yymmdd)

Packaging: 20 litres

Colours: Clear

CLP symbols:

CLP signal word: Danger

MAL code: 5-3

Protective gear:



In case of insufficient ventilation, use filter mask A1

Document date: 20-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro
+45 9610 5080 • info@promal.dk • www.promal.dk