

TDS og instruction

Mineralsk terpentin

Cleaner and thinner

Item number 910-0000xx PR number 2368598

UFI:



White spirit.

Areas of application

Cleaning of different substrates before painting.
Cleaning of tools that have been used for oil painting.
Thinning of oil based paint.

Treatment

Apply white spirit with a brush or a cloth.
Avoid application methods that create spray mist.
The treated surface can advantageously be processed mechanically.
Most oil points can be diluted using 10-20% white spirit, however follow the instructions from the supplier of the paint.

When used as a diluent, 10-20% is normally added.
Follow the instructions from the supplier of the paint material.

Limitations

Do not work with white spirit on hot surfaces as harmful vapours will form.

Warning/safety

Avoid static electricity, hot sparks, open flame and contact with strong oxidizing agents.

Use gloves. Avoid contact with skin, hair and eyes.
Use eye protection and respirator with filter A1.

Keep out of reach of children.

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

Type: Solvent

Areas of application:
Cleaning and dilution

Active substances:
White spirit 100%

Density: Approx. 0.8 kg/l ISO 2811

Concentration: 100%

Boiling point: 175-225°C

Flash point: 64°C

Self-ignition temperature: 240°C

Odours: Characteristic

Warning:
Avoid contact with strong oxidizing agents
Avoid heating and contact with ignition sources

Application temperature:
Developed for use at 0°C-25°C
(substrate and surroundings)

Cleaning tools:
Water

Storage:
Store at +0°C-+25°C, not in direct sunlight and inaccessible to children

Shelf life:
Min. 24 months from production date when stored correctly
(Batch no. yymmdd)

Packaging: 2½ og 20 litres

Colours: Clear

CLP symbols:

CLP signal word: Danger

MAL code: 3-1

Protective gear:



Apply filter mask A1

Document date: 20-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro
+45 9610 5080 • info@promal.dk • www.promal.dk