



TASSO A/S CAST IRON BAR STANDARD STOCK PROGRAMME WEIGHT LIST

Round profile	
Dimensions	Weight kg/m
Ø 25	3,7
Ø 30	5,3
Ø 35	7,2
Ø 40	9,4
Ø 41	9,9
Ø 45	11,9
Ø 46	12,4
Ø 50	14,7
Ø 51	15,3
Ø 55	17,7
Ø 56	18,4
Ø 60	21,1
Ø 61	21,8
Ø 65	24,8
Ø 66	25,5
Ø 70	28,7
Ø 71	29,6
Ø 75	33,0
Ø 76	33,9
Ø 80	37,5
Ø 81	38,5
Ø 85	42,4
Ø 86	43,4
Ø 90	47,5
Ø 91	48,6
Ø 95	52,9
Ø 96	54,1
Ø 100	58,7
Ø 101	59,8
Ø 105	64,7
Ø 106	65,9
Ø 110	71,0
Ø 111	72,3
Ø 115	77,6
Ø 116	78,9
Ø 120	84,5
Ø 121	85,9
Ø 125	91,7
Ø 130	99,2
Ø 135	106,9

Round profile	
Dimensions	Weight kg/m
Ø 140	115,0
Ø 145	123,3
Ø 150	132,0
Ø 155	140,9
Ø 160	150,2
Ø 165	159,7
Ø 170	169,6
Ø 180	190,1
Ø 190	211,8
Ø 200	234,7
Ø 210	258,7
Ø 220	284,0
Ø 230	310,4
Ø 240	337,9
Ø 250	366,7
Ø 260	396,6
Ø 270	427,7
Ø 280	459,8
Ø 290	493,2
Ø 300	527,8
Ø 310	563,6
Ø 320	600,6
Ø 340	678,0
Ø 360	760,1
Ø 380	846,9
Ø 400	938,4
Ø 420	1034,7
Ø 440	1135,6
D-section	
Dimensions	Weight kg/m
D 53 / 28	31,4
D 70 / 40	42,0
D 82 / 44	50,5
D 88 / 49	54,5
D 95 / 54	59,3
D 105 / 57,5	66,6
D 110 / 60	70,3
D 114 / 62	73,3
D 120 / 65	77,7

Square profile	
Dimensions	Weight kg/m
40x40	11,9
45x45	15,1
50x50	18,7
55x55	22,6
60x60	26,9
65x65	31,6
70x70	36,6
75x75	42,0
80x80	47,8
85x85	54,0
90x90	60,5
95x95	67,4
100x100	74,7
110x110	90,4
115x115	98,8
120x120	107,5
130x130	126,2
135x135	136,1
140x140	146,6
150x150	168,0
155x155	179,4
160x160	191,2
165x165	200,3
170x170	215,8
180x180	241,9
190x190	269,5
200x200	298,7
210x210	329,3
220x220	361,4
240x240	430,1
260x260	504,8
270x270	544,4
280x280	585,5
290x290	628,0

TASSO A/S minimum and non-standard production runs	
Diameter (mm)	Weight (tons)
Below 60	5
61-80	6
81-100	8
101-150	10
151-200	16
201-300	20
301 and above	24

- Non-standard size production can vary between 90%-120% of the order. This should be accepted by customer.
- Minimum runs are for EN-GJL-250C and EN-GJS-500-7C (EN-GJS-400-15C). Other grades need specific enquiry.
- Minimum quantity to be increased by 25% if rectangle ratio is equal or more than 1 to 2 (e.g 100x200).
- Standard production length is 3 m (gross length 3080 mm). Other lengths available subject to discussion and special order.
- Valid from 01/03/201