

## Lave ferrit-pottemagneter Gevindhul

Maks. driftstemperatur 120° C.

Kappe i blødt stål.

Forzinket.

Gevindstuds.



Produkt-nr.	Diameter	Kapnehøjde <i>mm</i>	Højde i alt	Genvindstørrelse	Vægt <i>kg</i>	Trækraft	Stk./pakning
<b>E860</b>	10	4,5	11	M3	0,003	0,4	20
<b>E861</b>	13	4,5	11,5	M3	0,005	1,0	20
<b>E862</b>	16	4,5	11,5	M3	0,006	1,8	20
<b>E863</b>	20	6	13	M3	0,011	3,0	10
<b>E864</b>	25	7	15	M4	0,022	4,0	10
<b>E865</b>	32	7	15	M4	0,032	8,0	5
<b>E866</b>	36	8	16	M4	0,045	10,0	5
<b>E867</b>	40	8	18	M5	0,060	12,5	5
<b>E868</b>	47	9	17	M4	0,090	18,0	1
<b>E869</b>	50	10	22	M6	0,110	22,0	1
<b>E870</b>	57	10,5	18,5	M4	0,145	28,0	1
<b>E871</b>	63	14	30	M8	0,240	35,0	1
<b>E872</b>	80	18	34	M10	0,520	60,0	1
<b>E873</b>	90	20	40	M10	0,820	70,0	1
<b>E874</b>	100	22	42	M12	0,940	90,0	1
<b>E875</b>	125	26	50	M14	1,720	130,0	1