

Strato S-20

The mid-range Strato model for measurement probes and dial gauges can be used in any type of mechanical system. Pre-tensioning cannot be set.



S-20.10 with switch magnet (M)



S-20.20 with pot magnet (TM)
(permanent)



S-20.30 with anyform magnet (AM)
(permanent)



S-20.60 with anyform magnet (AMO), which can be switched on and off with a turning handle

Model	Overall height mm	Radius of movement mm	Fine adjustment ^{1,2} mm	Base size mm	Holding strength approx. N	Order no.
S-20 F + M	310	200	Ø 8	60 x 50 x 55	800	S-20.10
S-20 F + TM	335	200	Ø 8	Ø 40 x 30	300	S-20.20
S-20 F + AM	310	200	Ø 8	77 x 48 x 55	600	S-20.30
S-20 F	255	200	Ø 8	-	-	S-20.50
S-20 F + AMO	310	200	Ø 8	91 x 52 x 55	600	S-20.60

All models without dial gauge/dial test indicator

¹ Microfine adjustment with dovetail and mounting hole

² US standard: microfine adjustment with 3/8" diameter hole results in order number nnnn.n5 (e.g.: S-20.15)

Strato M-28

The large Strato model additionally features steplessly adjustable pre-tensioning to protect the instrument.



M-28.10 with switch magnet (M)



M-28.20 with vacuum base (V)



M-28.40 with sliding granite base (G)

Model	Overall height mm	Radius of movement mm	Fine adjustment ^{1,2} mm	Base size mm	Holding strength approx. N	Order no.
M-28 F + M	390	280	Ø 8	60 x 50 x 55	800	M-28.10
M-28 F + V	365	280	Ø 8	Ø 88 x 27	-	M-28.20
M-28 F	335	280	Ø 8	-	-	M-28.30
M-28 F + G	385	280	Ø 8	150 x 120 x 50 x 50	-	M-28.40
M-28 F + SM ³	390	280	Ø 8	75 x 50 x 55	1000	M-28.50

All models without dial gauge/dial test indicator

¹ Microfine adjustment with dovetail and mounting hole

² US standard: microfine adjustment with 3/8" diameter hole results in order number nnnn.n5 (e.g.: S-28.15)

³ with switch magnet (SM)