



AX 885A



Z
12-24


HSS-
Co5

Type
N



DIN
885A

HSS-Co5 Side Milling Cutter



d ₁ mm	s mm	d mm	Z	Uncoated Part No.	f _r Roughing mm/Z	f _f Finishing mm/Z
50,0	4	16	12	AX885A5040	0,052	0,050
50,0	5	16	12	AX885A5050	0,052	0,050
50,0	6	16	12	AX885A5060	0,052	0,050
50,0	8	16	12	AX885A5080	0,052	0,050
50,0	10	16	12	AX885A50100	0,052	0,050
63,0	4	22	12	AX885A6340	0,062	0,062
63,0	5	22	12	AX885A6350	0,062	0,062
63,0	6	22	12	AX885A6360	0,062	0,062
63,0	8	22	12	AX885A6380	0,062	0,062
63,0	10	22	12	AX885A63100	0,062	0,062
63,0	12	22	12	AX885A63120	0,062	0,062
63,0	14	22	12	AX885A63140	0,062	0,062
63,0	16	22	12	AX885A63160	0,062	0,062
63,0	18	22	12	AX885A63180	0,062	0,062
80,0	4	27	14	AX885A8040	0,072	0,070
80,0	5	27	14	AX885A8050	0,072	0,070
80,0	6	27	14	AX885A8060	0,072	0,070
80,0	8	27	14	AX885A8080	0,072	0,070
80,0	10	27	14	AX885A80100	0,072	0,070
80,0	12	27	14	AX885A80120	0,072	0,070
80,0	14	27	14	AX885A80140	0,072	0,070
80,0	16	27	14	AX885A80160	0,072	0,070
80,0	18	27	14	AX885A80180	0,072	0,070
80,0	20	27	14	AX885A80200	0,072	0,070
100,0	4	32	14	AX885A10040	0,082	0,080
100,0	5	32	14	AX885A10050	0,082	0,080
100,0	6	32	14	AX885A10060	0,082	0,080
100,0	8	32	14	AX885A10080	0,082	0,080
100,0	10	32	14	AX885A100100	0,082	0,080
100,0	12	32	14	AX885A100120	0,082	0,080
100,0	14	32	14	AX885A100140	0,082	0,080
100,0	16	32	14	AX885A100160	0,082	0,080
100,0	18	32	14	AX885A100180	0,082	0,080
100,0	20	32	14	AX885A100200	0,082	0,080
100,0	25	32	14	AX885A100250	0,082	0,080
125,0	6	32	16	AX885A12560	0,092	0,090
125,0	8	32	16	AX885A12580	0,092	0,090
125,0	10	32	16	AX885A125100	0,092	0,090
125,0	12	32	16	AX885A125120	0,092	0,090
125,0	14	32	16	AX885A125140	0,092	0,090
125,0	16	32	16	AX885A125160	0,092	0,090
125,0	18	32	16	AX885A125180	0,092	0,090
125,0	20	32	16	AX885A125200	0,092	0,090
125,0	25	32	16	AX885A125250	0,092	0,090
125,0	28	32	16	AX885A125280	0,092	0,090
160,0	6	40	18	AX885A16060	0,092	0,090
160,0	8	40	18	AX885A16080	0,092	0,090
160,0	10	40	18	AX885A160100	0,092	0,090
160,0	12	40	18	AX885A160120	0,092	0,090
160,0	14	40	18	AX885A160140	0,092	0,090
160,0	16	40	18	AX885A160160	0,092	0,090
160,0	18	40	18	AX885A160180	0,092	0,090
160,0	20	40	18	AX885A160200	0,092	0,090
160,0	25	40	18	AX885A160250	0,092	0,090
160,0	32	40	18	AX885A160320	0,092	0,090
200,0	8	40	24	AX885A20080	0,092	0,090
200,0	10	40	24	AX885A200100	0,092	0,090
200,0	12	40	24	AX885A200120	0,092	0,090
200,0	14	40	24	AX885A200140	0,092	0,090
200,0	16	40	24	AX885A200160	0,092	0,090
200,0	18	40	24	AX885A200180	0,092	0,090
200,0	20	40	24	AX885A200200	0,092	0,090
200,0	25	40	24	AX885A200250	0,092	0,090
200,0	32	40	24	AX885A200320	0,092	0,090

Material	Steel	Cast	Alu	Plastics
Tensile strength/ Hardness	< 850 N/mm ²	< 240 N/mm ²	< 450 N/mm ²	
V _c (m/min) Finishing	40	40	190	120
V _c (m/min) Roughing	30	25	170	100