



Codice - Code

Materiale - Material	HSSE	HSSE	HSSE	HSSE
Imbocco - Chamfer	C	C	B	B
Tolleranza - Tolerance	6H	6H	6H	6H
Rivestimento - Coating				TiN

M d mm	p mm	L mm	I mm (C-B)	d3 h9 mm	S h12 mm		in stock	in stock	in stock	in stock
2	0,4	45	8	1,4	-	1,6	o		o	ro
2,5	0,45	50	9	1,8	-	2	o		o	ro
3	0,5	56	11	2,2	-	2,5	o		o	o
3,5	0,6	56	13	2,5	2,1	2,9	o		o	ro
4	0,7	63	12-13	2,8	2,1	3,3	o		o	o
4,5	0,75	70	13-16	3,5	2,7	3,7	o		o	ro
5	0,8	70	13-16	3,5	2,7	4,2	o		o	o
6	1	80	15-19	4,5	3,4	5	o		o	o
7	1	80	15-19	5,5	4,3	6	o		o	ro
8	1,25	90	18-22	6	4,9	6,8	o		o	o
9	1,25	90	18-22	7	5,5	7,8	o		o	ro
10	1,5	100	20-24	7	5,5	8,5	o		o	o
11	1,5	100	20-24	8	6,2	9,5	o		o	ro
12	1,75	110	23-29	9	7	10,2	o	o	o	o
14	2	110	25-30	11	9	12	o	o	o	o
16	2	110	25-32	12	9	14	o	o	o	o
18	2,5	125	30-34	14	11	15,5	o	o	o	ro
20	2,5	140	30-34	16	12	17,5	o	o	o	ro
22	2,5	140	30-34	18	14,5	19,5	o	o	o	ro
24	3	160	36-38	18	14,5	21	o	o	o	ro
27	3	160	36-38	20	16	24	o	o	o	ro
30	3,5	180	40-45	22	18	26,5	o	o	o	ro
33	3,5	180	42-50	25	20	29,5	o		o	ro
36	4	200	50-56	28	22	32	o		o	ro
39	4	200	50-60	32	24	35	o		o	ro
42	4,5	200	56-60	32	24	37,5	o		o	ro
45	4,5	220	56-65	36	29	40,5	o		o	ro
48	5	250	63-70	36	29	43	o		o	ro
52	5	250	63-70	40	32	47	o		o	ro

r su richiesta - on demand