



HSS-PM HSS-PM Line

Serie/Series
27105

Frese per sedi di linguette americane (Woodruff)
Woodruff cutters

COATING
Skin

W
A RICHIESTA
ON REQUEST

F
A RICHIESTA
ON REQUEST

H

UNI 8263
DIN 850B
ISO

Cod. Art.	M-TK (HSS-E)	X-85 (PM Co 8,5%)	COATED	D +0,05 -0	S +0 -0,02	ds	L1	L	dh6	λ°	Z
271051020 AM	CM	CMX		10,5	2	4	9	50	6	13	8
271051025 AM	CM	CMX		10,5	2,5	4	9	50	6	13	8
271051030 AM	CM	CMX		10,5	3	4,2	8	50	6	13	8
271051302 AM	CM	CMX		13,5	2	4,6	12	56	10	15	8
271051303 AM	CM	CMX		13,5	3	4,6	12	56	10	15	8
271051304 AM	CM	CMX		13,5	4	4,6	12	56	10	15	8
271051603 AM	CM	CMX		16,5	3	4,6	12	56	10	15	8
271051604 AM	CM	CMX		16,5	4	4,6	12	56	10	15	8
271051605 AM	CM	CMX		16,5	5	5	9,5	56	10	15	8
271051606 AM	CM	CMX		16,5	6	5	9,5	56	10	15	8
271051903 AM	CM	CMX		19,5	3	5,6	17,5	63	10	15	10
271051904 AM	CM	CMX		19,5	4	5,6	17,5	63	10	15	10
271051905 AM	CM	CMX		19,5	5	6	16	63	10	15	10
271051906 AM	CM	CMX		19,5	6	6,5	15	63	10	15	10
271052204 AM	CM	CMX		22,5	4	6	17	63	10	13	10
271052205 AM	CM	CMX		22,5	5	6	17	63	10	13	10
271052206 AM	CM	CMX		22,5	6	6,5	13	63	10	13	10
271052208 AM	CM	CMX		22,5	8	6,5	13	63	10	13	10
271052505 AM	CM	CMX		25,5	5	7,5	12	63	10	15	12
271052506 AM	CM	CMX		25,5	6	7,5	12	63	10	15	12
271052507 AM	CM	CMX		25,5	7	7,5	12	63	10	15	12
271052508 AM	CM	CMX		25,5	8	7,5	12	63	10	15	12
271052806 AM	CM	CMX		28,5	6	8,5	10	63	10	13	12
271052807 AM	CM	CMX		28,5	7	8,5	10	63	10	13	12
271052808 AM	CM	CMX		28,5	8	8,5	10	63	10	13	12
271052810 AM	CM	CMX		28,5	10	9,3	13	71	12	13	12
271053206 AM	CM	CMX		32,5	6	8,5	16	71	12	15	12
271053207 AM	CM	CMX		32,5	7	8,5	16	71	12	15	12
271053208 AM	CM	CMX		32,5	8	8,5	16	71	12	15	12
271053210 AM	CM	CMX		32,5	10	9,3	13	71	12	15	12
271054510 AM	CM	CMX		45,5	10	11	13	71	12	13	12



Z8÷12



MATERIALI LAVORABILI / WORKPIECE MATERIALS

serie
séries
27105

TITANIO
TITANIUM

HRSA
HRSA

ACCIAI
INOSSIDABILI
STAINLESS
STEELS

MATERIALI
NON FERROSI
NON FERROUS
MATERIALS

LEGHE
LEGGERE
LIGHT ALLOYS

ACCIAI
STEELS

GHISE
CAST IRON

● consigliata/recommended ● accettabile/acceptable ○ non consigliata/not recommended