



HSS-PM
HSS-PM Line

Serie/Series

29105

Frese a profilo costante concavo
Form relieved concave milling cutters

COATING	N	UNI 4499 DIN ISO
Skin		

Cod. Art.	M-TK (HSS-E)	COATED	R H11	Djs16	S	dH7	Z
291050100 AM	AMX		1	56	8	22	14
291050150 AM	AMX		1,5	56	8	22	14
291050200 AM	AMX		2	56	9	22	14
291050250 AM	AMX		2,5	56	10	22	14
291050300 AM	AMX		3	63	12	22	14
291050350 AM	AMX		3,5	63	14	22	14
291050400 AM	AMX		4	63	16	22	14
291050450 AM	AMX		4,5	63	18	22	12
291050500 AM	AMX		5	63	20	22	12
291050550 AM	AMX		5,5	63	22	22	12
291050600 AM	AMX		6	70	24	22	12
291050650 AM	AMX		6,5	70	26	22	12
291050700 AM	AMX		7	70	28	22	12
291050750 AM	AMX		7,5	80	30	27	12
291050800 AM	AMX		8	80	32	27	12
291050850 AM	AMX		8,5	80	34	27	12
291050900 AM	AMX		9	90	36	27	12
291050950 AM	AMX		9,5	90	38	27	12
291051000 AM	AMX		10	90	40	27	12
291051100 AM	AMX		11	100	42	27	12
291051200 AM	AMX		12	100	44	27	12
291051250 AM	AMX		12,5	100	46	27	12
291051300 AM	AMX		13	100	48	27	12
291051400 AM	AMX		14	100	50	27	12
291051500 AM	AMX		15	110	53	32	12
291051600 AM	AMX		16	110	56	32	12
291051700 AM	AMX		17	110	59	32	12
291051800 AM	AMX		18	125	62	32	12
291051900 AM	AMX		19	125	66	32	12
291052000 AM	AMX		20	125	70	32	12

Z12÷14



MATERIALI LAVORABILI / WORKPIECE MATERIALS

serie séries	TITANIO TITANIUM	HRSA HRSA	ACCIAI INOSSIDABILI STAINLESS STEELS	MATERIALI NON FERROSI NON FERROUS MATERIALS	LEGHE LEGGERE LIGHT ALLOYS	ACCIAI STEELS	GHISE CAST IRON
29105	●	●	●	○	○	●	●

● consigliata/recommended ● accettabile/acceptable ○ non consigliata/not recommended