



Split hole punch TriCut+™ for sheet steel (S235) and stainless steel

- 1 With 3-fold split
- 2 With UNF fine thread
- 3 With 4 crosshair markings for simple, central alignment



EDELSTAHL
STAINLESS STEEL

"The max. material thickness for which a hole punch can be used always depends on the screw and draw bolts used."

Usable up to a material thickness of:

- 2.5 mm steel sheet with 3/4" (19.0 mm) screw or draw bolt
- 2.0 mm steel sheet with 7/16" (11.1 mm) screw or draw bolt

Split hole punch TriCut+™ - sets



All sets are supplied in heavy-duty practical plastic cases.

Ø mm	15.2	16.2	18.6	19.0	20.4	22.5	25.4	28.3	30.5	31.7	32.5	34.6	37.0	38.0	40.5	43.2	47.0	49.6	50.5	54.0	60.0	61.5	63.5
Ø metric	-	M 16	-	-	M 20	-	M 25	-	-	-	M 32	-	-	-	M 40	-	-	-	M 50	-	-	-	M 63
Ø PG	9	-	11	-	13	16	-	21	-	-	-	-	29	-	-	-	36	-	-	42	48	-	-
Ø Inch	-	-	-	3/4"	-	7/8"	1"	-	1-7/32"	1-1/4"	-	-	-	1-1/2"	-	1-11/16"	-	1-15/16"	-	2-1/8"	-	2-3/8"	2-1/2"
Ø Conduit	-	-	-	-	-	1/2"	-	3/4"	-	-	-	1"	-	-	-	1 1/4"	-	1 1/2"	-	-	-	2"	-
Prod.-No.																							
01652		•			•		•				•				•								
01653		•			•		•				•				•				•				•
01645						•		•				•				•		•				•	
01646			•				•			•				•					•				