




„Absolute“ Electr. Digital Caliper • IP54 DIN 862


- top model for industry purpose
- spray water proof acc. to DIN 40050 / IEC 60529
- with Bluetooth data transmission (max. 5m distance)

- mechanic parts stainless, hardened steel
- large LCD display with clear reading, digit height 13 mm
- Absolute-System latest generation, with "ORIGIN"-system
- measuring jaws finely ground and lapped
- On/Off-button, with fixing screw, with thumbroll
- mm/inch switchable, zero-setting at any position
- incl. 2 x 3V battery (type CR2032, art.-no. 2002093), with operation manual



Option

- data transfer via Bluetooth, art. no. 2023106, see page 304



				ABSOLUTE
	ORIGIN	Bluetooth		
	DIN	CE	TC	WARRANTY 3 YEARS


ART NO	mm / inch	mm / inch	mm	mm					ART NO CC
202420	150 / 6	0.01 / 0.0005	0.01	0.02	40	16.5	flat	0.150	2094101
202421	200 / 8	0.01 / 0.0005	0.01	0.02	50	19.5	flat	0.175	2094101
202422	300 / 12	0.01 / 0.0005	0.01	0.03	60	20.5	flat	0.215	2094101



Electr. Digital Caliper • IP54 DIN 862

- top model for industry purposes
- with glass rail for more accuracy
- spray water proof acc. to DIN 40050 / IEC 60529

- sturdy quality, stainless steel, hardened
- large LCD display with clear reading, 9 mm digit height
- jaws finely ground and lapped, with fixing screw
- On/Off button, with ABS/INC measuring system
- graduation in mm or inch, zero setting at any position
- incl. 1x 3 V battery (type CR2032, art.-no.: 2002093), with operation manual



ABS/INC			DIN	
CE	TC	WARRANTY 3 YEARS		


ART NO	mm / inch	mm / inch	mm	mm					ART NO CC
202160-2	150 / 6	0.01 / 0.0005	0.01	0.02	40	16	flat	0.160	2094101
202161-2	200 / 8	0.01 / 0.0005	0.01	0.03	50	19.5	flat	0.195	2094101
202162-2	300 / 12	0.01 / 0.0005	0.01	0.03	60	20.5	flat	0.230	2094101




Electr. Digital Caliper DIN 862

- top model for professional workshop use
- with glass rail for more accuracy
- housing with metal cover and metal buttons
- with data output (mini USB)

- sturdy quality, stainless steel, hardened
- with or without thumbroll (included, for self installation)
- large LCD display with clear reading, 9 mm digit height
- jaws finely ground and lapped
- On/Off-button, with flat or round depth gauge
- mm/inch switchable, zero setting at any position
- incl. 1x 3 V battery (type CR2032, art.-no.: 2002093), with operation manual



with removeable thumbroll



	DIN	CE	TC	WARRANTY 2 YEARS

Option

- data transfer via cable, art.-no. 209001, see page 304

ART NO	mm / inch	mm / inch	mm	mm					ART NO CC
202040-3	150 / 6	0.01 / 0.0005	0.01	0.02	40	16.5	flat	0.165	2094101
202041-3	200 / 8	0.01 / 0.0005	0.01	0.03	50	19.5	flat	0.195	2094101
202042-3	300 / 12	0.01 / 0.0005	0.01	0.03	60	20.5	flat	0.230	2094101
202043-3	150 / 6	0.01 / 0.0005	0.01	0.02	40	16.5	round	0.165	2094101