

Spirit Levels

Spirit Levels „NIVEAU NORM“

- top quality spirit levels with plane surfaces

- rugged light alloy rectangular profile, from up 1500 mm length with extrem solid wallthickness
- with 1x horizontal vial and 1x vertical vial
- barrel-shaped vials with patented SOLID built-in system, permanent fixed and constantly aligned with the profile
- surfaces in stratosilver elocated
- measuring accuracy adjusted by electronical adjustment and at final inspection
- measuring accuracy in normal position 0.5 mm/m = 0.029°, with reversal measurement minimum 0.75 mm/m = 0.043°

art-no. 714100 - 714110

- with strong adhesive magnet in the measurement base



plane, rectangular aluminium profile,
extruded and warm cured



ART NO 714100 - 714110

with strong adhesive magnet in the measurement base

ART NO 714000 - 714010



WARRANTY
3 YEARS

ART NO 714100 - 714110



WARRANTY
3 YEARS

ART NO	→ mm ←				max.	
					vial	KG
714000	200	50 x 22	X	0.5 mm/m = ± 0.029°	0.142	
714001	300	50 x 22	X	0.5 mm/m = ± 0.029°	0.194	
714002	400	50 x 22	X	0.5 mm/m = ± 0.029°	0.250	
714003	500	50 x 22	X	0.5 mm/m = ± 0.029°	0.299	
714004	600	50 x 22	X	0.5 mm/m = ± 0.029°	0.358	
714005	800	50 x 22	X	0.5 mm/m = ± 0.029°	0.422	
714006	1000	50 x 22	X	0.5 mm/m = ± 0.029°	0.565	
714007	1200	50 x 22	X	0.5 mm/m = ± 0.029°	0.682	
714008	1500	50 x 22	X	0.5 mm/m = ± 0.029°	1.105	
714009	1800	50 x 22	X	0.5 mm/m = ± 0.029°	1.226	
714010	2000	50 x 22	X	0.5 mm/m = ± 0.029°	1.366	
714100	200	50 x 22	✓	0.5 mm/m = ± 0.029°	0.210	
714101	300	50 x 22	✓	0.5 mm/m = ± 0.029°	0.266	
714102	400	50 x 22	✓	0.5 mm/m = ± 0.029°	0.383	
714103	500	50 x 22	✓	0.5 mm/m = ± 0.029°	0.482	
714104	600	50 x 22	✓	0.5 mm/m = ± 0.029°	0.509	
714105	800	50 x 22	✓	0.5 mm/m = ± 0.029°	0.614	
714106	1000	50 x 22	✓	0.5 mm/m = ± 0.029°	0.698	
714107	1200	50 x 22	✓	0.5 mm/m = ± 0.029°	0.809	
714108	1500	50 x 22	✓	0.5 mm/m = ± 0.029°	1.308	
714109	1800	50 x 22	✓	0.5 mm/m = ± 0.029°	1.554	
714110	2000	50 x 22	✓	0.5 mm/m = ± 0.029°	1.664	