CAST IRON BAR SPECIALIST



STANDARD STOCK PROGRAMME

Round profile	Grade		Round profile	Grade		Square profile	Grade		Minimum and non-standard production runs		
<u>Dimensions</u>	EN- GJL	EN- GJS	<u>Dimensions</u>	EN- GJL	EN- GJS	<u>Dimensions</u>	EN- GJL	EN- GJS	Diameter (mm)	Weight (tons)	
Ø 26*	✓		Ø 140	✓	✓	40x40	✓		Below 60	6	
Ø 31*	✓		Ø 145	✓	✓	45x45	✓		61-80	8	
Ø 36*	✓		Ø 150	✓	✓	50x50	✓	✓	81-100	8	
Ø 40		✓	Ø 155	✓		55x55	✓	✓	101-150	10	
Ø 41	✓		Ø 160	✓	✓	60x60	✓	✓	151-200	14	
Ø 45		✓	Ø 165	✓		65x65	✓	✓	201-300	22	
Ø 46	✓		Ø 170	✓	✓	70x70	✓	✓	301 and	Discuss with	
Ø 50		✓	Ø 180	✓	✓	75x75	✓	✓	above	foundry	
Ø 51	✓		Ø 190	✓	✓	80x80	✓	✓			
Ø 55		✓	Ø 200	✓	✓	85x85	✓				
Ø 56	✓		Ø 210	✓	√	90x90	✓	✓		ard production	
Ø 60		✓	Ø 220	✓	✓	95x95	✓	✓	_	etween 90-120% er. This should be	
Ø 61	✓		Ø 230	✓	✓	100x100	✓	✓		by customer.	
Ø 65		✓	Ø 240	✓	✓	110x110	✓	✓		.,	
Ø 66	✓		Ø 250	✓	✓	115x115	✓		 Minimum runs are for EN- GJL-250C and EN-GJS-500 7C (EN-GJS-400-15C). Other 		
Ø 70		✓	Ø 260	✓	✓	120x120	✓	✓			
Ø 71	✓		Ø 270	✓		130x130	✓	✓			
Ø 75		✓	Ø 280	✓	✓	140x140	√	✓	· ·	ed specific in-	
Ø 76	✓		Ø 290	✓	✓	150x150	√	✓	quiry.	·	
Ø 80		✓	Ø 300	✓	✓	155x155		✓		production length	
Ø 81	✓		Ø 320	✓	√	160x160	√	✓	• Standard r		
Ø 85		✓	Ø 340	✓	√	170x170	√	✓		0 mm gross	
Ø 86	✓		Ø 360	✓	√	180x180	√	✓		her lengths are	
Ø 91	✓	✓	Ø 380	✓	√	190x190	√			ubject to discus-	
Ø 95		✓	Ø 400	✓	√	200x200	√	✓	sion and sp	pecial order	
Ø 96	✓					210x210		✓			
Ø 100		✓	D-section	Gra	de	220x220	√	√	\	n 26/08/2022	
Ø 101	✓			EN-C	GJL-	240x240	√	√	• <u>valid from</u>		
Ø 105		✓	<u>Dimensions</u>	150C		260x260	√	√			
Ø 106	✓		D 53 / 28	✓		270x270	√		 *Availability 	/ upon request	
Ø 110		√	D 70 / 40	· ✓		280x280	√				
Ø 111	√		D 82 / 44	✓							
Ø 115		√	D 88 / 49	•							
Ø 116	✓		D 95 / 54	·							
Ø 121	✓	√	D 105 / 57,5	· ·							
Ø 125	√	√	D 110 / 60	·							

Ø 130

Ø 135

✓

D 114 / 62

D 120 / 65

CAST IRON BAR SPECIALIST



STANDARD STOCK PROGRAMME

Rectangle	Gra	ade	Rectangle	Grade		Minimum and non-standard production runs		
<u>Dimensions</u>	EN-GJL	EN-GJS	<u>Dimensions</u>	EN-GJL	EN-GJS	Diameter (mm)	Weight (tons)	
30x50	✓		90x110	✓	✓	Below 60	6	
40x50	✓		90x120	✓	✓	61-80	8	
40x60	✓		90x130	✓	✓	81-100	8	
40x70	✓		90x140	✓		101-150	10	
40x90	✓		100x110	✓	✓	151-200	14	
40x100	✓		100x120	✓		201-300	22	
40x110	✓		100x130	✓	✓	301 and above	Discuss with	
40x120	✓		100x150	✓		Sol alla above	foundry	
50x60	✓		100x200	✓				
50x70	✓	✓	110x120		✓			
50x80	✓		110x130	✓	✓	 Non-standa 	rd production	
50x90	✓		110x140	✓			tween 90-120%	
50x100	✓		120x140		✓	of the order	er. This should	
50x110	✓		120x160	✓	✓	be accepted	d by customer.	
50x120	✓		130x180	✓				
60x80	✓	✓				Minimum ru	uns are for EN-	
60x90	✓	✓				GJL-250C ar		
60x100	✓						-GJS-400-15C).	
60x110	✓					_	des need spe-	
60x120	✓					cific inquiry.		
70x80	✓	✓						
70x90	✓	✓				Standard pr		
70x100	✓	✓				<u>length</u> is 3m	•	
70x110	✓	✓				gross length	available sub-	
70x120	✓					_	ssion and spe-	
70x130	✓					cial order		
80x100	✓	✓						
80x110	✓					 Valid from 1' 	7/08/2022	
80x120	✓	✓				<u>valid Hofff I</u>	7,00,2022	
80x130		✓						
90x100	✓							