

Product Date: 08.08.2013 ZEW / Vertrieb BIEDA J Dept. specification Name:

Wellpappenwerk Delmenhorst

Customer: **PaperlinX**

7500 Holstebro

Article no. customer: 266063 Article no. supplier: 177789

Size (internal dimension): 750 x 1.150 x

Zuschnitt 0110 Typ of packaging: Packaging drawing (CAD): Weight of packaging: D110012 340 g ± 8 %

Board grade 1): Klingele code: VDW 1.03 E BRAUN/BRAUN

E418.105.418

130 g/m² Testliner braun 90 g/m² Wellenstoff Paper grades 2): Outer liner

E-flute 130 g/m² Testliner braun Inner liner

0

Recycled content: ca. 100 %

Printing: Colours 3):

Closure: unverschlossen

0 St./Pack Delivery: Bundle 1 x 1.000 St.

Stacking Pieces on pallet 1.000 Hight incl. pallet 1.800 mm Pallet type **Euro-Palette** Pallet cover Wellpappe

Pallet strapping 2-Fach quer (breit)

Pallet wrapping

Recommended stock and

converting conditions: 18 - 23 degree Celsius and 45 - 65 % rel. humidity

Remark: Replaces all former editions.

¹⁾ Target values in accordance with the current DIN 55 468-1 standard, for E-flute these are recommended values only. The technical properties of our corrugated board products can only be guaranteed 6 months after delivery if correct storage is assured. Manufacturing tolerances to VDW Inspection Catalogue.

²⁾ All papers comply with the current statutory provisions of the German Federal Institute for Risk Assessment (BfR) and with Recommendation XXXVI of its Plastics Committee. The basis weight tolerances are ± 4 %, a customary value worldwide. Due to scheduling or production engineering reasons, the application of similar or better papers is possible.

³⁾ The water-based flexographic printing inks comply to the EuPlA exclusion list for printing inks.