

Current version: 2.2.0, issued: 25.03.2013 Replaced version: 2.1.0, issued: 14.03.2012 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Paint Marker Ink (black) contained in: edding 750, edding 751, edding 755, edding 780 paint marker

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in drawliners

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Directive 67/548/EEC or 1999/45/EC

F; R11

R67

R66

2.2 Label elements

Labelling according to Directive 1999/45/EC

Hazard symbols



Highly flammable

R phrases

11 Highly flammable.

Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

S phrases

24 Avoid contact with skin. 37 Wear suitable gloves.

Labelling information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

2.3 Other hazards

No data available.



Current version: 2.2.0, issued: 25.03.2013 Replaced version: 2.1.0, issued: 14.03.2012 Region: GB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)

Hazardous ingredients

Hazardous ingredients								
No	Substance name		Additional information					
	CAS / EC / Index /	Classification 67/548/EEC	Concentration			%-b.w.		
	REACH no							
1	ETHYLCYCLOHEXANE							
	1678-91-7	F; R11	>	20.00	-	<	40.00	%-b.w.
	216-835-0	Xn; R65						
	-							
	-							
2	NAPHTHA (PETROLEUM), HYDROTREATED HEAVY							
	64742-48-9	F; R11	>	10.00	-	<	30.00	%-b.w.
	265-150-3	Xn; R65						
	649-327-00-6	R67						
	-	R66						
3	CARBON BLACK							
	1333-86-4	-	>	5.00	-	<	15.00	%-b.w.
	215-609-9							
	-							
	-							

Full Text for all R-phrases: pls. see section 16

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.).

After ingestion

Rinse mouth thoroughly with water. Summon a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam; extinguishing powder; Carbon dioxide



Current version: 2.2.0, issued: 25.03.2013 Replaced version: 2.1.0, issued: 14.03.2012 Region: GB

Unsuitable extinguishing media

No data available.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppres gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When picked up, treat material as prescribed under heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation, if necessary). Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

None known

7.3 Specific end use(s)

No data available.



Current version: 2.2.0, issued: 25.03.2013 Replaced version: 2.1.0, issued: 14.03.2012 Region: GB

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.		
1	CARBON BLACK	1333-86-4		215-609-9		
	List of approved workplace exposure limits (WELs) / EH40					
	Carbon black					
	STEL	7	mg/m³			
	TWA	3.5	mg/m³			

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product . Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour			
liquid			
black			
Odour			
aromatic			
Odour threshold			
No data available			
pH value			
No data available			
Boiling point / boiling range			
Value	116	°C	



Trade name: Paint Marker Ink (black) contained in: edding 750, edding 751, edding 755, edding 780 pain

Current version: 2.2.0, issued: 25.03.2013 Replaced version: 2.1.0, issued: 14.03.2012 Region: GB

Melting point / melting range No data available				
Decomposition point / decomposition range No data available				
Flash point Value			7	°C
			•	
Ignition temperature Value	200	_	262	°C
	200	-	202	C
Auto-ignition temperature No data available				
Oxidising properties No data available				
Explosive properties No data available				
Flammability (solid, gas) No data available				
Lower flammability or explosive limits Value			0.90	9/ vol
			0.90	% vol
Upper flammability or explosive limits				
Value			8.40	% vol
Vapour pressure				
Value			10 28	mm Hg
Reference temperature			20	°C
Vapour density				
No data available				
Evaporation rate				
No data available				
Relative density				
No data available				
Density				
Value Reference temperature			0.96 20	g/cm³ °C
			20	
Solubility in water	incoluble			
Remarks	insoluble			
Solubility(ies)				
No data available				
Partition coefficient: n-octanol/water				
No data available				
Viscosity			1150	
Value Type	dynamic		1150	mPa*s
1390	ayriaiiille			

9.2 Other information

Other information	
No data available.	



Trade name: Paint Marker Ink (black) contained in: edding 750, edding 751, edding 755, edding 780 pain

Current version: 2.2.0, issued: 25.03.2013 Replaced version: 2.1.0, issued: 14.03.2012 Region: GB

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

No data available.

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

No data available

Acute dermal toxicity

No data available

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.



Trade name: Paint Marker Ink (black) contained in: edding 750, edding 751, edding 755, edding 780 pain

Current version: 2.2.0, issued: 25.03.2013 Replaced version: 2.1.0, issued: 14.03.2012 Region: GB

SECTION 12: Ecological information

12.1 Toxicity

Fish toxicity	
No data available	

Daphnia toxicity

No data available

Algae toxicity

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information

Ecological data are not available.

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3 Classification code F1 Packing group Ш Hazard identification no. 33 **UN** number UN1263 Technical name **PAINT** Special Provision 640 640D Tunnel restriction code D/E Label 3



Trade name: Paint Marker Ink (black) contained in: edding 750, edding 751, edding 755, edding 780 pain

Current version: 2.2.0, issued: 25.03.2013 Replaced version: 2.1.0, issued: 14.03.2012 Region: GB

14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263
Proper shipping name PAINT
EmS F-E+S-E
Label 3

14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263
Proper shipping name Paint
Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, pls. see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Remarks

Annex I, part 2, category 7 b

15.2 Chemical safety assessment

No data available.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

EC Directive 67/548/EC resp. 1999/45/EC as amended in each case.

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EC

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the R-, H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

R65 Harmful: may cause lung damage if swallowed.

Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183, D-21107 Hamburg

Tel.: +49 40 / 79 02 36 300 Fax: +49 40 / 79 02 36 357 e-mail: umco@umco.de

This information is based on our present state of knowledge and experience.

The security data sheet describes products with a view to the security requirements.

However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.