

Data sheet for SKUB 2X10 Battransp STD

Application

Art. No: 4483

10mm² Bare Copper conductor acc. to IEC 60228,6

| Properties | Nominal Value | Unit |
|----------------------------|---------------|-------|
| Wire in Conductor, Approx. | 294 | pcs |
| Wire diameter | 0,20 | mm |
| Resistance, max at 20°C. | 1,910 | Ω/km |
| Copper weight | 2*96 | Kg/km |

Insulation of 10mm² conductor acc. to EN 50363,3


| Properties | Nominal Value | Unit |
|---------------------|----------------|------|
| Material | PVC | |
| Temperature range | -25 to +70 | °C |
| Nom. Wall thickness | 1,00 | mm |
| Min. Wall thickness | 0,80 | mm |
| Nom. Outer diameter | 6,4 ± 0,15 | mm |
| Color | Red, Dark-Blue | |

Outer sheath of 2x10 conductor acc. to EN 50363,4-1

| Properties | Nominal Value | Unit |
|---------------------|------------------------|------|
| Material | Soft PVC | |
| Temperature range | -35 to +70 | °C |
| Nom. Wall thickness | 1,0 | mm |
| Min. Wall thickness | 0,75 | |
| Nom. Outer diameter | 8,4 ± 0,5 x 18,3 ± 0,5 | mm |
| Color | Transparent | |

Specific properties

| Properties | Nominal Value | Unit |
|------------------|--------------------|------|
| Voltage range | 450/750 | V |
| Flame properties | Pass IEC 60332-1-2 | |
| RoHS directive | Pass | - |
| Marking | Customer choice | |



2019-06-14