

RELi³ON[®]

insightTM SERIES



Your supplier
GACELL
The right battery
GACELL A/S · Slotens 17 · 7500 Holsleben · DK
+45 96102 961 · www.gacell-power.dk

LiFePO4

INTELLIGENT FEATURES

Unlimited Parallel Connections

- Intelligent battery-to-battery balancing
- Additive continuous and peak currents
- Scale as needed

Heatsink Design

- Strategically located
- Unique passive cooling
- Prevents over-heating of critical components

Dual M8 Terminals (Insert and Stud)

- Ample space for connections

LED Indicator

- Provides State of Charge (SOC)

Unique BMS Design

- Microcontroller-based design
- Intuitive software
- Solid State Switch for ultra-fast response times
- High-resolution internal measurements
- Non-volatile historical data
- CANbus communication
- Sleep mode capability

RELi³ON[®] | DATA SHEET

MODEL

| | |
|-------------|------------|
| Part Number | 24V060-GC2 |
|-------------|------------|

FUNCTIONAL SPECIFICATIONS

| | |
|---------------------------|---------------------|
| Nominal Voltage | 25.6 |
| Cell Chemistry | LiFePO4 |
| Cell Type | Prismatic |
| Ampere-hour Capacity | 60Ah |
| Watt-hour Capacity | 1.536kWh |
| Specific Energy | 128Wh/kg |
| Charge Efficiency | 99% |
| Impedance (50% SOC, 1kHz) | <100mΩ |
| Cycles @ 80% DOD | >3500 |
| Parallel Capable | Yes (unlimited) |
| Series Capable | No (max 24V system) |

MECHANICAL SPECIFICATIONS

| | |
|----------------------------|--|
| BCI Size | GC2 / GC8 |
| Dimensions (LxWxH) | 10.2 x 7.1 x 10.9 in (260 x 180 x 276 mm) |
| Weight | 34.4 lbs (15.6 kg) |
| Case Material | ABS |
| Stud Terminal | M8 X 1.25 - 20 |
| Insert Terminal | M8 X 1.25 - 20 |
| Torque | 79.7-88.5 in-lbs. 6.6 - 7.4 ft-lbs. 9-10 N-m |
| Handles | Molded |
| Ingress Protection Marking | IP67 |
| Case Flame Rating | UL94 V-0 |

DISCHARGE SPECIFICATIONS

| | |
|---|----------------------|
| Continuous Discharge Current | 100A |
| Peak Discharge Current | 240A - 15 sec |
| Peak Discharge Current | 440A - 30 msec |
| Short Circuit Protection | 880A - 610 μsec |
| Protection Recover | Automatic |
| Low Voltage Disconnect | 20V - 5 sec (2.5vpc) |
| Low Voltage Reconnect | Automatic |
| Self-Discharge per Month @ 25°C in OFF mode | 2.80% |

CHARGE SPECIFICATIONS

| | |
|----------------------------|------------------------|
| Continuous Charge Current | ≤ 60A |
| Disconnect Charge Current | 65A - 5 sec |
| Recommended Charge Voltage | 27.6V |
| Float Voltage | 27.2V |
| High Voltage Disconnect | 29.6V (3.7vpc) (4 sec) |
| High Voltage Reconnect | Automatic |
| Temperature Compensation | None |



- 1. Dual M8 Terminals (insert & stud)
- 2. CANbus Input
- 3. CANbus Output
- 4. Power Button
- 5. SOC/Status LEDs
- 6. Heatsink
- 7. Vent
- 8. Lifting Brackets

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|-----------------------------------|
| Charge Temperature | 32°F to 131°F (0°C to 55°C) |
| Discharge Temperature | -22°F to 149°F (-30°C to 65°C) |
| Operating Humidity | <90% RH |
| Storage Temperature | -4°F to 95°F (-20°C to 35°C) |
| Storage Humidity | 25 to 85% RH |

CERTIFICATIONS

| |
|--|
| UL2580 (Cell) File Number: MH63797 |
| UL2271 (Battery Pack) File Number: MH64262 |
| CE (Battery Pack) |
| IEC 62133 (Battery Pack) |
| UN38.3 (Battery Pack) |

SHIPPING CLASSIFICATION

| |
|------------------|
| UN 3480, Class 9 |
|------------------|

APPLICATIONS

| |
|-----------------------|
| Floor Machines |
| Pallet Jacks |
| Aerial Work Platforms |
| Utility Vehicles |

COMPATIBLE ACCESSORIES

| |
|-----------------------------|
| InSight Remote Button |
| InSight Fuel Gauge (CANbus) |

