

Specifications

Nominal Voltage		12 V
Capacity (25°C)	10HR(10.8V)	5.0Ah
	5HR(10.5V)	4.6Ah
	1HR(9.60V)	3.53Ah
Dimension	Length	90 ± 1mm (3.54inch)
	Width	70 ± 1mm (2.76inch)
	Height	101 ± 1mm (3.98inch)
	Total Height	107 ± 1mm (4.21inch)
Approx. Weight		1.65kg (3.64lbs) ± 5%
Terminal type		T1/T2
Internal resistance (Fully charged, 25°C)		Approx. 30mΩ
Capacity affected by temperature (20HR)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-discharge (25°C)	3 month	Remaining Capacity: 91%
	6 month	Remaining Capacity: 82%
	12 month	Remaining Capacity: 65%
Nominal operating temperature		25°C ± 3°C (77°F ± 5°F)
Operating temperature range	Discharge	-15°C ~ 50°C (5°F ~ 122°F)
	Charge	-10°C ~ 50°C (14°F ~ 122°F)
	Storage	-20°C ~ 50°C (-4°F ~ 122°F)
Float charging voltage(25°C)		13.60 to 13.80V Temperature compensation: -18mV/°C
Cyclic charging voltage(25°C)		14.50 to 14.90V Temperature compensation: -30mV/°C
Maximum charging current		1.5A
Terminal material		Copper
Maximum discharge current		75A(5 sec.)
Designed floating life(20°C)		15 years

- ◆ Absorbent glass mat technology;
- ◆ Recognized by UL & CE;
- ◆ ABS container.




Constant Current Discharge Characteristics (A, 25°C)

F.V/TIME	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
9.60V	20.0	12.6	10.1	5.64	3.53	1.93	1.39	1.11	0.95	0.52	0.27
9.90V	19.5	12.3	9.88	5.53	3.48	1.92	1.38	1.10	0.93	0.52	0.27
10.2V	18.6	11.7	9.51	5.36	3.39	1.90	1.37	1.10	0.93	0.51	0.27
10.5V	17.8	11.3	9.18	5.23	3.33	1.87	1.36	1.09	0.92	0.51	0.26
10.8V	16.8	10.7	8.71	5.04	3.22	1.83	1.32	1.05	0.89	0.50	0.26

Constant Power Discharge Characteristics (Watt, 25°C)

F.V/TIME	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
9.60V	224	142	115	64.7	40.9	22.6	16.4	13.2	11.3	6.15	3.32
9.90V	217	138	113	63.4	40.3	22.5	16.4	13.2	11.2	6.13	3.29
10.2V	208	133	109	61.4	39.2	22.3	16.3	13.0	11.1	6.10	3.28
10.5V	199	127	104	60.0	38.5	22.0	16.2	12.9	11.0	6.07	3.26
10.8V	188	120	99.2	57.8	37.3	21.4	15.7	12.6	10.7	5.95	3.20


Note: The above characteristics data can be obtained within three charge/discharge cycles.

**Dimensions****Terminal**


Terminal T1

Terminal T2


Discharge Characteristics(25°C)




Charging Characteristics(25°C)




Effect of Temperature on Capacity




Self-discharge Characteristics




The Relationship for Open Circuit Voltage and Residual Capacity (25°C)



The Relationship for Charging Voltage and Temperature



Floating Life on Temperature



Cycle Life on D.O.D.(25°C)

