



GACELL®

The right battery



Electrical specification

<u>Voltage:</u>	<input type="text" value="12"/>	V
<u>Capacity:</u>	<input type="text" value="110"/>	Ah
<u>Cold cranking current:</u>	<input type="text" value="750"/>	A, (EN)
<u>Cold cranking current:</u>	<input type="text" value="450"/>	A, (DIN)

Mechanical specification

<u>Dimensional group:</u>	<input type="text" value="-"/>	EN50342-2:2007
<u>ETN reference:</u>	<input type="text" value="G78GR31XD0_1"/>	
<u>DIN reference:</u>	<input type="text" value="-"/>	
<u>Sizes:</u>	<input type="text" value="336x173x225"/>	(L x W x H)
<u>Cell Layout:</u>	<input type="text" value="1"/>	
<u>Terminal Type:</u>	<input type="text" value="Dual (MARINE TWIN)"/>	

<u>Container</u>	Case	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
		Bottom hold down	<input type="text" value="B1"/>	Handles	<input type="text" value="BLACK"/>
	Lid	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
		Cover design	<input type="text" value="SMF"/>	Handles	<input type="text" value="BLACK"/>
	Vent cap	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
		Type	<input type="text" value="SMF"/>		

Test details

<u>Vibration resistance:</u>	<input type="text" value="V2"/>	<u>Water consumption:</u>	<input type="text" value="W3"/>
<u>Endurance resistance:</u>	<input type="text" value="E1"/>	<u>Charge retention:</u>	<input type="text" value="C2"/>

<u>Battery weight:</u>	<input type="text" value="14.80"/>	±0.80 (kg)
<u>Acid weight:</u>	<input type="text" value="9.10"/>	±0.50 (kg)
<u>Total battery weight:</u>	<input type="text" value="23.90"/>	±1.30 (kg)

Separator: Type: