

DATA SHEET
for GACELL 17331
According to EN 50342



Electrical specification

<u>Voltage:</u>	12V	(V)
<u>Capacity:</u>	100	(Ah)
<u>Cold cranking current:</u>	800	(A, EN)
<u>Cold cranking current:</u>	550	(A, DIN)

Mechanical specification

<u>Dimensional group:</u>	L5	EN50342-2:2009
<u>ETN reference:</u>	600 038 080	
<u>DIN reference:</u>	-	
<u>Sizes:</u>	353x175x190	(L x W x H)
<u>Cell Layout:</u>	0	
<u>Terminal Type:</u>	1	

Container

<u>Case</u>	Material	POLYPROPYLENE	Colour	BLACK
	Bottom hold down	B 3	Handles	-
<u>Lid</u>	Material	POLYPROPYLENE	Colour	BLACK
	Cover design	SMF	Handles	BLACK
<u>Vent cap</u>	Material	POLYPROPYLENE	Colour	BLACK
	Type	SMF		

Test details

<u>Vibration resistance:</u>	V2
<u>Endurance resistance:</u>	E1

<u>Battery weight:</u>	14.10	± %5	(kg)
<u>Acid weight:</u>	7.50	± %5	(kg)
<u>Total battery weight:</u>	21.60	± %5	(kg)

<u>Separator:</u>	Type:	PE
--------------------------	-------	-----------