DURACELL®
AUTOMOTIVE

GET STARTED!

TECHNICAL DATA SHEET

Type no.	DA 60T

Article no.	013560090801
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery

Electrical data	
Rated voltage	12V
Rated capacity	60 Ah (K20)
Cold start current	540 A (EN)

Dimensions and weights		
Box	LB2	
Length max.	241mm	
Width max.	175mm	
Box height max.	175mm	
Total height max.	175mm	
Battery weight	Ca. 15,0 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		72
Pallet ID		Euro pallet
Items per layer		18

Features	
Base hold-down	B13
Layout	0
Terminal	1
Separator	PE envelope separator
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - V2 - E1

Maintenance [1])	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage [2])	max. 14,8 V

[1]) All the listed values relate to room temperature +25° C
[2]) Recommendation with an external, voltage-regulated charge.
Attention: Temperature compensation in case of deviation!

Document prepared on 2018-09-06; Rights relating to changes and errors retained.
original

Din forhandler
GACELL®
The right battery
GACELL A/S - Sletten 17 - DK 7500 Holstebro - 961 02 961

Duracell Automotive c/o Banner GmbH
Banner Straße 1, A-4021 Linz, Tel.: +43/(0)732/38 88-0, Fax DW-21599
e-mail: info@duracell-automotive.com, **www.duracell-automotive.com**

duracell-automotive.com