

TECHNICAL DATA SHEET

Type no.	DA 63H	
Article no.	013563400801	
Standards	DIN EN 50342-1, 50342-2	
Application	Starter battery	
Electrical data		
Rated voltage	12V	
Rated capacity	63 Ah (K20)	
Cold start current	620 A (EN)	
Dimensions and weights		
Box	L2	
Length max.	241mm	
Width max.	175mm	
Box height max.	190mm	
Total height max.	190mm	
Battery weight	Ca. 16,5 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	72	
Pallet ID	Euro pallet	
Items per layer	18	
Features		
Base hold-down	B13	
Layout	0	
Terminal	1	
Separator	PE envelope separator	
Degassing	Battery with central degassing	
Flame arrester	Integrated	
Performance identification	W4 - C2 - V2 - E2	
Maintenance ¹⁾		
Water consumption	W4	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 3 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage ²⁾	max. 14,8 V	



- 1) All the listed values relate to room temperature +25° C
 2) Recommendation with an external, voltage-regulated charge.
 Attention: Temperature compensation in case of deviation!

Document prepared on 2018-09-06; Rights relating to changes and errors retained.
 original



GACELL A/S - Sletten 17 - DK 7500 Holstebro - 961 02 961

Duracell Automotive c/o Banner GmbH
 Banner Straße 1, A-4021 Linz, Tel.: +43/(0)732/38 88-0, Fax DW-21599
 e-mail: info@duracell-automotive.com, www.duracell-automotive.com



duracell-automotive.com