

TECHNICAL DATA SHEET

| | | |
|----------------------------------|--|--|
| Type no. | DA 72 | |
| Article no. | 013572090801 | |
| Standards | DIN EN 50342-1, 50342-2 | |
| Application | Starter battery | |
| Electrical data | | |
| Rated voltage | 12V | |
| Rated capacity | 72 Ah (K20) | |
| Cold start current | 670 A (EN) | |
| Dimensions and weights | | |
| Box | LB3 | |
| Length max. | 278mm | |
| Width max. | 175mm | |
| Box height max. | 175mm | |
| Total height max. | 175mm | |
| Battery weight | Ca. 17,5 kg (+/- 5 %) | |
| Electrolyte density | Approx. 1,28 kg/l | |
| Electrolyte | Diluted sulphuric acid | |
| Items/pallet | 64 | |
| Pallet ID | Euro pallet | |
| Items per layer | 16 | |
| Features | | |
| Base hold-down | B13 | |
| Layout | 0 | |
| Terminal | 1 | |
| Separator | PE envelope separator | |
| Degassing | Battery with central degassing | |
| Flame arrester | Integrated | |
| Performance identification | W4 - C2 - V2 - E1 | |
| Maintenance ¹⁾ | | |
| Water consumption | W4 | |
| Refill water | Distilled or demineralised (DIN 43530) | |
| Self-discharge | Approx. 3 % per month | |
| Charging current | Approx. 1/10 of the rated capacity | |
| Charging voltage ²⁾ | max. 14,8 V | |



- 1) All the listed values relate to room temperature +25° C
 2) Recommendation with an external, voltage-regulated charge.
 Attention: Temperature compensation in case of deviation!

Document prepared on 2018-09-06; Rights relating to changes and errors retained.
 original



GACELL A/S - Sletten 17 - DK 7500 Holstebro - 961 02 961

Duracell Automotive c/o Banner GmbH
 Banner Straße 1, A-4021 Linz, Tel.: +43/(0)732/38 88-0, Fax DW-21599
 e-mail: info@duracell-automotive.com, www.duracell-automotive.com

