


TECHNICAL DATA SHEET

Type no.	DS 70	
Article no.	010570440801	
Standards	DIN EN 50342-1, 50342-2	
Application	Starter battery	
Electrical data		
Rated voltage	12V	
Rated capacity	70 Ah (K20)	
Cold start current	640 A (EN)	
Dimensions and weights		
Box	LB3	
Length max.	278mm	
Width max.	175mm	
Box height max.	175mm	
Total height max.	175mm	
Battery weight	Ca. 17,0 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	64	
Pallet ID	Euro pallet	
Items per layer	16	
Features		
Base hold-down	B13	
Layout	0	
Terminal	1	
Separator	PE bag separator	
Degassing	Battery with central degassing	
Flame arrester	Integrated	
Performance identification	W4 - C2 - V1 - E1	
Maintenance ¹⁾		
Water consumption	W4	
Refill water	Destilliert oder entmineralisiert (DIN 43530)	
Self-discharge	Ca. 3 % pro Monat	
Charging current	Ca. 1/10 der Nennkapazität	
Charging voltage ²⁾	max. 14,8 V	



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge.

Attention: Temperature compensation in case of deviation!

Document prepared on 2018-09-06; Rights relating to changes and errors retained.
original



GACELL A/S - Sletten 17 - DK 7500 Holstebro - 961 02 961

Duracell Automotive c/o Banner GmbH

Banner Straße 1, A-4021 Linz, tel.: +43/(0)732/38 88-0, Fax DW-21599

e-mail: info@duracell-automotive.com, www.duracell-automotive.com



duracell-automotive.com