

TECHNICAL DATA SHEET



Type no.		AGM 670 01	
Article no.		016670010101	
EAN/GTIN no.		9005753101463	
Application		Starter- & on-board battery	
Electrical data			
Rated voltage		12V	
Rated capacity		170 Ah (K20)	
Cold start current		1000 A (EN)	
Dimensions and weights			
Box	B		
Length max.	513mm		
Width max.	223mm		
Box height max.	195mm		
Total height max.	220mm		
Battery weight	Ca. 46,0 kg (+/- 5 %)		
Electrolyte density		Approx. 1,32 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		21	
Pallet ID		Euro pallet	
Items per layer		7	
Features			
Base hold-down		B00	
Layout		3	
Terminal		1	
Separator		AGM separator	
Degassing		Battery with central degassing	
Flame arrester		Integrated	
Performance identification		W5 - C2 - V3+ - M3 (E4)	
Maintenance ¹⁾			
Water consumption		W5	
Refill water		Absolutely maintenance-free	
Self-discharge		Approx. 3 % per month	
Charging current		Approx. 1/20 of the rated capacity	
Charging voltage ²⁾		max. 14,8 V	

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2025-07-30; Rights relating to changes and errors retained.
original