

TECHNICAL DATA SHEET



Type no.		625 13
Article no.		010625130101
EAN/GTIN no.		9005753005358
Application		Starter battery
Electrical data		
Rated voltage		12V
Rated capacity		125 Ah (K20)
Cold start current		760 A (EN)
Dimensions and weights		
Box	COMPACT	
Length max.	345mm	
Width max.	172mm	
Box height max.	260mm	
Total height max.	283mm	
Battery weight	Ca. 35,0 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		36
Pallet ID		Euro pallet
Items per layer		12
Features		
Base hold-down		B00
Layout		1
Terminal		1
Separator		PE bag separator
Degassing		Battery with single degassing
Flame arrester		Not integrated
Performance identification		W3-C2-V2-E1
Maintenance ¹⁾		
Water consumption		W3
Refill water		Distilled or demineralised (DIN 43530)
Self-discharge		Approx. 5 % per month
Charging current		Approx. 1/10 of the rated capacity
Charging voltage ²⁾		max. 14,4 V

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.
original