

TECHNICAL DATA SHEET



Type no.		625 23	
Article no.		010625230100	
EAN/GTIN no.		9005753083530	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		125 Ah (K20)	
Cold start current		720 A (EN)	
Dimensions and weights			
Box	NATO 6TN		
Length max.	280mm		
Width max.	267mm		
Box height max.	213mm		
Total height max.	230mm		
Battery weight	Ca. 34,5 kg (+/- 5 %)		
Electrolyte density		Approx. 1,28 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		36	
Pallet ID		Euro pallet	
Items per layer		12	
Features			
Base hold-down		B00	
Layout		2	
Terminal		1	
Separator		PE bag separator	
Degassing		Battery with single degassing	
Flame arrester		Not integrated	
Performance identification		W3-C2-V2-E1	
Maintenance ¹⁾			
Water consumption		W3	
Refill water		Distilled or demineralised (DIN 43530)	
Self-discharge		Approx. 5 % per month	
Charging current		Approx. 1/10 of the rated capacity	
Charging voltage ²⁾		max. 14,4 V	



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.
original