

MONBAT Premium SMF NP77L3X0_1 75 Ah

According to EN 50342


Premium

SEALED MAINTENANCE FREE



The right battery

Electrical specification

Voltage:	12V
Capacity C ²⁰ :	75 Ah
Cold cranking current:	720 A [EN]
Cold cranking current:	430 A [DIN]

Mechanical specification

Dimensional group:	L3
ETN reference:	575 083 072 SMF
DIN reference:	57583
Dimensions ^A in mm (LxWxH):	278x175x190
Cell Layout:	0
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B13
	Colour	Grey

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Grey

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Grey



Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Grey

Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V2	E2

Weight^B

Battery weight in kg:	12.50
Acid weight in kg:	5.80
Total battery weight in kg:	18.30

Layout

Hold-down

Separator

Type	PE
------	-----------

^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

^{B.} Weight may vary ±5%.