

MONBAT Premium ASIA K256J4X0_1 50 Ah

According to EN 50342 / JIS D 5301



Premium
SEALED MAINTENANCE FREE



The right battery
GACELL A/S · Sletten 17 · 7500 Holstebro · DK
+45 961 02 961 · www.gacell-power.dk

Electrical specification

| | |
|---------------------------------|--------------------|
| Voltage: | 12V |
| Capacity C²⁰: | 50 Ah |
| Cold cranking current: | 400 A [EN] |
| Cold cranking current: | 235 A [DIN] |

Mechanical specification

| | |
|--|------------------------|
| Dimensional group: | NS60 |
| ETN reference: | 550 055 040 SMF |
| DIN reference: | - |
| Dimensions^A in mm (LxWxH): | 237x128x220 |
| Cell Layout: | 1 |
| Terminal Type: | 3 |

Container

| | | |
|-------------|-------------------------|----------------------|
| Case | Material | Polypropylene |
| | Bottom hold-down | B0 |
| | Colour | Grey |

| | | |
|------------|---------------------|----------------------|
| Lid | Material | Polypropylene |
| | Cover design | SMF |
| | Colour | Grey |

| | | |
|------------------|-----------------|----------------------|
| Vent caps | Material | Polypropylene |
| | Type | SMF |
| | Colour | Grey |

| | | |
|----------------|-----------------|----------------------|
| Handles | Material | Polypropylene |
| | Position | Top - on lid |
| | Colour | Grey |


Battery classification as per EN 50342-6

| | | | |
|--------------------------|-------------------------|-----------------------------|------------------------|
| Water consumption | Charge retention | Vibration resistance | Endurance Level |
| W4 | C2 | V2 | E2 |

Weight^B

| | |
|------------------------------------|--------------|
| Battery weight in kg: | 8.60 |
| Acid weight in kg: | 3.80 |
| Total battery weight in kg: | 12.40 |

Layout



Hold-down



Separator

| | |
|-------------|-----------|
| Type | PE |
|-------------|-----------|

A. Height taken from bottom of the battery to the highest point on the vary depending on type of terminal.

B. Weight may vary ±5%.