

EC01BX3_1 170 Ah

According to EN 50342



SMF series
HEAVY-DUTY VEHICLES



Your supplier
GACELL
The right battery
GACELL A/S · Sletten 17 · 7500 Holstebro · DK
+45 961 02 961 · www.gacell-power.dk

Electrical specification

Voltage:	12V
Capacity C ²⁰ :	170 Ah
Cold cranking current:	1000 A [EN]
Cold cranking current:	590 A [DIN]

Mechanical specification

Dimensional group:	B
ETN reference:	670 043 100 SMF
DIN reference:	67043
Dimensions ^A in mm (LxWxH):	513x223x223
Cell Layout:	3
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Sides - on container
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W3	C2	V2	E2

Weight^B

Battery weight in kg:	28.30
Acid weight in kg:	13.70
Total battery weight in kg:	42.00

Layout



Hold-down



Separator

Type	PE with Glass Mat
------	--------------------------

- ^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
^{B.} Weight may vary ±5%.