

EC34CX3_1 230 Ah

According to EN 50342



SMF series

HEAVY-DUTY VEHICLES



GACELL A/S · Sletten 17 · 7500 Holstebro · DK
+45 961 02 961 · www.gacell-power.dk

Electrical specification

Voltage:	12V
Capacity C²⁰:	230 Ah
Cold cranking current:	1250 A [EN]
Cold cranking current:	740 A [DIN]

Mechanical specification

Dimensional group:	C
ETN reference:	730 011 125 SMF
DIN reference:	73011
Dimensions^A in mm (LxWxH):	514x276x242
Cell Layout:	3
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Sides - on container
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W3	C2	V2	E2

Weight^B

Battery weight in kg:	36.90
Acid weight in kg:	19.00
Total battery weight in kg:	55.90

Layout



Hold-down



Separator

Type	PE with Glass Mat
-------------	--------------------------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.