

MONBAT Formula ASIA KX44J3X0_1 35 Ah

According to EN 50342 / JIS D 5301



Formula Asia

JIS SEALED MAINTENANCE FREE



GACELL A/S · Stetten 17 · 7500 Holstebro · DK
+45 961 02 961 · www.gacell-power.dk

Electrical specification

Voltage:	12V
Capacity C²⁰:	35 Ah
Cold cranking current:	300 A [EN]
Cold cranking current:	180 A [DIN]

Mechanical specification

Dimensional group:	NS40
ETN reference:	535 020 030 SMF
DIN reference:	53520
Dimensions^A in mm (LxWxH)	197x128x220
Cell Layout:	0
Terminal Type:	3

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V1	E2

Weight^B

Battery weight in kg:	6.70
Acid weight in kg:	3.10
Total battery weight in kg:	9.80

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.