

MONBAT Formula ASIA KX45J4XB0_1 45 Ah

According to EN 50342 / JIS D 5301


Formula Asia

JIS SEALED MAINTENANCE FREE



Your supplier
GACELL®
The right battery

GACELL A/S · Sletten 17 · 7500 Holstebro · DK
+45 961 02 961 · www.gacell-power.dk

Electrical specification

Voltage:	12V
Capacity C ²⁰ :	45 Ah
Cold cranking current:	330 A [EN]
Cold cranking current:	200 A [DIN]

Mechanical specification

Dimensional group:	NS60
ETN reference:	545 023 033 SMF
DIN reference:	-
Dimensions ^A in mm (LxWxH):	237x128x220
Cell Layout:	0
Terminal Type:	3

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black


Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black

Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V1	E2

Weight^B

Battery weight in kg:	7.70
Acid weight in kg:	3.90
Total battery weight in kg:	11.60

Layout

Hold-down

Separator

Type	PE
------	-----------

^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

^{B.} Weight may vary ±5%.