

MONBAT Formula A67B2P0_1 65 Ah

According to EN 50342



Formula

SEALED MAINTENANCE FREE



Your supplier



The right battery

GACELL A/S · Sletten 17 · 7500 Holstebro · DK
+45 961 02 961 · www.gacell-power.dk

Electrical specification

Voltage:	12V
Capacity C²⁰:	65 Ah
Cold cranking current:	580 A [EN]
Cold cranking current:	360 A [DIN]

Mechanical specification

Dimensional group:	LB2
ETN reference:	565 005 058 SMF
DIN reference:	56505
Dimensions^A in mm (LxWxH)	242x175x175
Cell Layout:	0
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B14
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V1	E1


Weight^B

Battery weight in kg:	10.10
Acid weight in kg:	4.50
Total battery weight in kg:	14.60

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.